

ri-magic® LED / ri-magic® HPLED

HIGH PERFORMANCE LED EXAMINATION LIGHT FOR DIAGNOSIS AND PROCEDURES.

NEW: HIGH POWER VERSION (HPLED)

green efficiency

ri-magic® LED

Design for examination couch and desk
incl. universal clamp
230 V/120 V Art. No.: 6230

Wall design
230 V/120 V Art. No.: 6240

Floor design
230 V/120 V Art. No.: 6250

ri-magic® HPLED

Floor design
230 V/120 V Art. No.: 6252

Transformers
230 V/120 V Art. No.: 11340

Other accessories
Stand with adapter incl. base
with 5 casters and tube
Art. No.: 11343
Adapter part between stand
and lamp arm
Art. No.: 11344
Wall fixture
Art. No.: 11345
Universal clamp
Art. No.: 11346

- High performance LED, 6.500 Kelvin.
- Lifetime of the lamp up to 50.000 hours.
- Significantly less heating and energy loss.
- Focusing device at the front of the light head.
- Highly flexible, long special arm can be bent in all directions.
- Rheostat handle for infinitely variable regulation of light intensity.
- Wide-range power cord for 230V/120V.
- Available with a choice of plugs to suit the electrical outlets in your country upon request.
- Available as mobile, wall and examination table or desk design.



- Sturdy mobile base made of fibreglass and chrome plated pole.
- Diameter 54 cm.
- Easy to move due to low friction castors (antistatic, two castors can be locked).
- Power supply attached to the pole (ri-magic® HPLED only).

ri-magic® LED

Distance

Lux max

Circle of light max. Ø

Circle of light min. Ø

1.000 mm / 39.37 inch	800 mm / 31.50 inch	600 mm / 23.62 inch	400 mm / 15.75 inch	200 mm / 7.87 inch
15.000	20.000	30.000	45.000	55.000
340 mm / 13.39 inch	270 mm / 10.63 inch	215 mm / 8.47 inch	155 mm / 6.10 inch	90 mm / 1.57 inch
40 mm / 1.58 inch	35 mm / 1.38 inch	30 mm / 1.18 inch	25 mm / 0.98 inch	20 mm / 0.79 inch

ri-magic® HPLED

Distance

Lux max

Circle of light max. Ø

Circle of light min. Ø

1.000 mm / 39.37 inch	800 mm / 31.50 inch	600 mm / 23.62 inch	400 mm / 15.75 inch	200 mm / 7.87 inch
20.000	32.000	55.000	100.000	170.000
500 mm / 19.69 inch	400 mm / 15.75 inch	320 mm / 12.60 inch	230 mm / 9.05 inch	130 mm / 5.12 inch
80 mm / 3.15 inch	60 mm / 2.36 inch	50 mm / 1.97 inch	35 mm / 1.38 inch	20 mm / 0.79 inch

ri-magic® LED