

NEW 315 DV NEW 315 DVS (SLOW SPEED)

315MM SWIVEL HEAD COLDSAW











- Italian made quality
- Swivel head 45° left & right
- Trigger switch operation

 Quick locking double vice for burr free cutting
- Blade protection clutch, suitable for cutting profile steels or tube where multiple material thicknesses are being cut in 1 pass. The clutch will protect the cutting teeth and material when passing from the thin easier to cut material into the thick harder to cut material.
- · Incorporated recirculating mechanical coolant system
- Adjustable material stop for repetitive production
- Safety emergency stop switch
- 12 months warranty
- Comes complete with blade
- Optional stand available
- Part# MC-STAND315
- . Slow speed (20rpm) model also available designed specifically for cutting stainless-steel. This model is supplied with higher flow, electric coolant pump.

Part No.	MC-NEW315DV-1		MC-NEW315DV-3		MC-NEW315DVS-3			
Motor	2hp		3hp		3hp			
	Single Phase (24	Single Phase (240V)		Three Phase (415V)		Three Phase (415V)		
Blade Speed	Single Sp	eed rpm	2 Speed 40 / 80rpm		2 Speed Slow 20 / 40rpm			
51 1 01	70	ipiii						
Blade Size	315mm							
Blade Bore	32mm							
Weight	170kg							
Cutting Capacity								
Cutting Angle			O					
90°	65mm	(90mm	85mm		120 x 70mm		
45° (L&R)	60mm	8	30mm	70mm		80 x 70mm		

OPTIONAL ACCESSORIES & CONSUMABLES



ROLLER CONVEYORS

- Straight & V-Shape Single Roller Conveyors
- 3m length, 300mm 600mm width Conveyors



SYNTHETIC METAL WORKING FLUID

Cutting fluid designed for use with MACC coldsaws, bandsaws & metal working machinery that use a recirculating coolant system with fluid storage tank.

Part No.	Description
MF-5LITRE	5 Litre MACC Synthetic Metal Working Fluid
MF-20LITRE	20 Litre MACC Synthetic Metal Working



Made In It<mark>al</mark>y

HIGH-SPEED STEEL DM05 (M2) COLD SAW BLADES

Part No.	Diameter	Thickness	Bore	# Teeth
C3152532-140	315mm	2.5mm	32mm	140
C3152532-160	315mm	2.5mm	32mm	160
C3152532-180	315mm	2.5mm	32mm	180
C3152532-200	315mm	2.5mm	32mm	200
C3152532-220	315mm	2.5mm	32mm	220

MACE