

AR615GB

Rewinda Grease Hose Reel - 15m x 6.3mm ID***10
YEAR
WARRANTY**

Materials & Workmanship

***2
YEAR
WARRANTY**

Wearing Components

REWINDA

May 2025

The new Alemlube AR615GB Rewinda Grease Hose Reel is an industrial quality hose storage & retrieval system featuring a high pressure wire braid hose.

This grease hose reel is suitable for industries needing cost effective grease delivery.

The Rewinda range has been researched, designed and engineered in conjunction with our long-standing, industry leading plastic covered hose reel partner, with the result being an exciting range of innovative, safe, ergonomic, durable and aesthetically pleasing hose reels.

Replacing the S Series as released in 2008, this new versatile and complete range meets market needs and is set to exceed industry expectations.

The patented speed rewind control system, included on all models, ensures that the hose retracts at a safe and steady speed, resulting in a safe operating environment, minimising the chance of damage to workshop equipment, and in some instances, customers' vehicles.

The unique, and also patented, stop-at-any-point latching system secures the hose at the exact desired length each and every time. The sliding guide system ensures that the hose returns neatly and evenly onto the barrel assembly, and the next level UV stabilised covers won't fade over time.

With a 10 year warranty on materials and workmanship and a no exclusions 2 year warranty on wearing parts such as o'rings, seals, hose assemblies, springs and bushes, the new Rewinda Series of hose reels is set to be the new on-point hose storage and retrieval solution in mining, construction, agriculture, transport and automotive sectors in Australia, New Zealand and Papua New Guinea.

SPECIFICATIONS, FEATURES & BENEFITS

- High pressure SAE 100R2 AT wire braid hose
- High grade impact resistant UV stabilised covers won't fade over time
- Patented speed rewind control system ensures that the hose retracts at a safe & steady speed with speed control brake system
- Patented stop-at-any-point latching system secures the hose at the exact desired length every time
- Sliding guide system ensures that the hose returns neatly & evenly on to the barrel assembly
- Detachable steel mounting bracket enables 180° hose reel rotation & fits other leading brands
- 15m x 6.3mm ID hose & 0.9m lead in hose
- 1/4" BSPT(m) inlet & outlet connections
- 1/4" BSPT(f) hose reel inlet thread
- Maximum working pressure of 5,800 psi (400 bar)
- Working temperature of -40°C to +100°C
- Weight of 16kg

