

AR1220CAB

Rewinda Compressed Air Hose Reel - 20m x 12mm ID



Materials & Workmanship



Wearing Components

**REWINDA**

February 2025

The new Alemlube AR1220CAB Rewinda Compressed Air Hose Reel is an industrial quality hose storage & retrieval system. **Featuring a highly flexible & durable hybrid polymer hose, crimped hose ends, an integral carry handle, detachable mounting bracket & a stop at any point latching mechanism to secure the hose at the desired length.**

With the covers manufactured from high-quality, impact-resistant & UV stabilised polypropylene, the AR1220CAB Rewinda Compressed Air Hose Reel utilises a heavy-duty internal spring assembly that easily retrieves the hose when partially or fully extended.

The new model is supplied with a Gen3 hybrid polymer hose, a speed control brake system, a new fully serviceable modern design & updated mounting brackets that can be used with the Alemlube S Series hose reels and other leading brands.

Suitable for use in mine sites, automotive, transport, manufacturing, agricultural & civil contractor workshops this compressed air hose reel is ideal for use with tyre gauges, pneumatic drills, impact wrenches, angle grinders & ratchets.

Mountable on the wall, floor or ceiling the AR1220CAB Rewinda Compressed Air Hose Reel is designed & engineered to go the distance when operating in the challenging work environments that are often encountered in Australia & New Zealand.

SPECIFICATIONS, FEATURES & BENEFITS

- Gen3 hybrid polymer hose
- High grade impact resistant UV stabilised covers
- Automatic & positive latching mechanism with speed control break system
- Stop at any point with a latching mechanism that secures the hose at the desired length
- Sliding guide system ensures that the hose returns neatly & evenly on to the barrel assembly
- Rubber grip on the hose assists during hose rewind & retrieval
- Detachable steel mounting bracket enables 180° hose reel rotation
- High flow swivel & fluid path
- Updated mounting brackets fits other leading brands
- 20m x 12mm ID hose & 0.9m lead in hose
- 1/2" BSPT(m) inlet/outlet connections
- 1/2" BSPT(f) hose reel inlet thread
- Maximum working pressure of 300 psi (20 bar)
- Working temperature of -40°C to +80°C
- Weight of 14kg
- Dimensions of 580mm (L) x 480mm (H) x 270mm (W)