





	1	2	3	4	5	6	7	8																									
A	<table><tr><th>Richtlänge Datum length [mm]</th><th>Längentoleranz Length tolerance</th><th>Satztoleranz Set tolerance [mm]</th></tr><tr><td>605 < L_p ≤ 900</td><td>± 1%</td><td>2</td></tr><tr><td>901 < L_p ≤ 2000</td><td>± 1%</td><td>4</td></tr><tr><td>2001 < L_p ≤ 2500</td><td>± 1%</td><td>6</td></tr><tr><td>2501 < L_p ≤ 3550</td><td>± 1%</td><td>8</td></tr></table>			Richtlänge Datum length [mm]	Längentoleranz Length tolerance	Satztoleranz Set tolerance [mm]	605 < L _p ≤ 900	± 1%	2	901 < L _p ≤ 2000	± 1%	4	2001 < L _p ≤ 2500	± 1%	6	2501 < L _p ≤ 3550	± 1%	8	Prinzip-Skizze Principle sketch 		<table><tr><th colspan="3">Profil / Section: X13 / AX</th></tr><tr><th>b [mm]</th><th>h [mm]</th><th>α [°]</th></tr><tr><td>13,0 ± 0,7</td><td>7,7 ± 0,8</td><td>39,0 ± 2</td></tr></table> Aufbau des Riemens: 1. Deckgewebe 2. Polyester 3. Chloropren-Mischung mit quer gerichteten Fasern V-Belt construction: 1. Fabric 2. Polyester 3. CR compound with transverse oriented fiber			Profil / Section: X13 / AX			b [mm]	h [mm]	α [°]	13,0 ± 0,7	7,7 ± 0,8	39,0 ± 2	A
Richtlänge Datum length [mm]	Längentoleranz Length tolerance	Satztoleranz Set tolerance [mm]																															
605 < L _p ≤ 900	± 1%	2																															
901 < L _p ≤ 2000	± 1%	4																															
2001 < L _p ≤ 2500	± 1%	6																															
2501 < L _p ≤ 3550	± 1%	8																															
Profil / Section: X13 / AX																																	
b [mm]	h [mm]	α [°]																															
13,0 ± 0,7	7,7 ± 0,8	39,0 ± 2																															
B	Kennzeichnungsbeispiel / Marking example: <table><tr><td>-</td><td>Made in ...</td><td>optibelt S-TX M=S</td><td>X13 2030 L_p AX 79</td><td>Antistatic ISO 1813</td><td><table><tr><td>1</td></tr><tr><td>2</td></tr></table></td><td>●</td></tr><tr><td colspan="2">Werkscodes / Plant code</td><td colspan="2">Profil und Länge / Section and Length</td><td colspan="3">Jahreszeichen / Year code</td></tr></table>								-	Made in ...	optibelt S-TX M=S	X13 2030 L _p AX 79	Antistatic ISO 1813	<table><tr><td>1</td></tr><tr><td>2</td></tr></table>	1	2	●	Werkscodes / Plant code		Profil und Länge / Section and Length		Jahreszeichen / Year code			B								
-	Made in ...	optibelt S-TX M=S	X13 2030 L _p AX 79	Antistatic ISO 1813	<table><tr><td>1</td></tr><tr><td>2</td></tr></table>	1	2	●																									
1																																	
2																																	
Werkscodes / Plant code		Profil und Länge / Section and Length		Jahreszeichen / Year code																													
C	Längen-Messbedingungen nach DIN 2215 und ISO 4183 Length measurement according to DIN 2215 and ISO 4183 <table><tr><td rowspan="9"></td><td>d_d [mm]</td><td>95,50 ± 0,05</td></tr><tr><td>U_d [mm]</td><td>300</td></tr><tr><td>d_a [mm]</td><td>102,10 ± 0,05</td></tr><tr><td>b_d [mm]</td><td>11,00</td></tr><tr><td>α [°]</td><td>34 ± 10'</td></tr><tr><td>t_{min} [mm]</td><td>12</td></tr><tr><td>Q [N]</td><td>200</td></tr><tr><td colspan="2">L_d = 2a + U_d</td></tr><tr><td colspan="2">L_a = 2a + U_a</td></tr></table>									d _d [mm]	95,50 ± 0,05	U _d [mm]	300	d _a [mm]	102,10 ± 0,05	b _d [mm]	11,00	α [°]	34 ± 10'	t _{min} [mm]	12	Q [N]	200	L _d = 2a + U _d		L _a = 2a + U _a		C					
	d _d [mm]	95,50 ± 0,05																															
	U _d [mm]	300																															
	d _a [mm]	102,10 ± 0,05																															
	b _d [mm]	11,00																															
	α [°]	34 ± 10'																															
	t _{min} [mm]	12																															
	Q [N]	200																															
	L _d = 2a + U _d																																
	L _a = 2a + U _a																																
D	Wir beraten Sie gerne über die Produkteigenschaften und -anpassungen bei besonderen Anforderungen. Bitte beachten Sie auch die Hinweise in den Optibelt Dokumentationen. Irrtümer und technische Änderungen vorbehalten. www.optibelt.com, © Optibelt GmbH We would be pleased to offer advice about technical characteristics and drive design as well as special requirements. Further information can be found in Optibelt documentation. Subject to technical modification and change, errors and omissions excepted. www.optibelt.com, © Optibelt GmbH						optibelt SUPER TX M=S		D																								
	1	2	3	4	5	6	7	8																									