

SPECIFICATION

Surface Mounted Paper Towel Dispenser shall hold and dispense 400 standard single-fold paper towels and shall be fabricated of alloy 18-8 stainless steel, grade 304, 22 gauge. Towel dispensing slot shall have a fully deburred edge for snag-free dispensing and user safety. Dispenser door shall be attached to bottom of unit with a full length 5mm diameter stainless steel multi-staked piano hinge. Structural assembly of body and door components shall be of welded construction. Door shall be provided with a refill view indicator and be held closed with a tumbler lock. All exposed surfaces shall be No. 4 satin finish and be protected during shipment with a PVC film easily removable after installation.

INSTALLATION

Unit is surface mounted on wall or partition using No. 10 self tapping screws (supplied by others). For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.


OPERATION

Towels are self-feeding until supply is depleted. Unit may be reloaded with a partial load in place and will continue to feed properly. Low level of towel supply is indicated from 30% capacity to approximately 15% level.

WARRANTY

One year.

Surface Mounted Paper Towel Dispenser shall be Model No. 10-0245-SS as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

