



SPECIFICATION

Toilet Roll Holder Double Controlled Delivery Surface Mounted shall hold and dispense all standard core roll tissue, up to 152 mm in diameter and be fabricated of cast aluminum with a satin matte silver-gray finish. The “no waste” rocking action spindles shall be fabricated of impact resistant, ABS thermoplastic and be theft resistant with a concealed release mechanism. Spindles shall rotate 1/2 revolution for each operation and return to original position. Roll core shall not be removable until tissue is exhausted.

INSTALLATION

Unit is surface mounted on wall or partition using No 10 self tapping screws (supplied by others). For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

OPERATION

Spindles revolve 1/2 revolution for each operation and then return to original position. Roll core prevents access to release pin and cannot be removed from spindle until exhausted. Unit is replenished by releasing a concealed pin which in turn releases a spring lock mechanism on spindle. Spindles operate independently.

WARRANTY

One year.


OPTION

10-0264-1A with uncontrolled delivery

10-0264-12 with controlled delivery & key lock

10-0264-1A2 with uncontrolled delivery & key lock

Toilet Roll Holder, Double, Controlled Delivery shall be Model No. 10-0264-1 as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

