



SPECIFICATION

Surface Mounted Surgical Soap Dispenser shall dispense 0.47 litres of soap or antiseptic solution. Dispenser/ Valve unit shall be constructed of chrome-plated brass body with stainless steel and plastic internal parts. Soap "globe" shall be fabricated of white polyethylene.

INSTALLATION

Unit is secured to a wall plate which is surface mounted to wall or partition using No.10 self tapping screws (supplied by others). For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use.

SOAP REQUIREMENTS

Proper usage of this dispenser requires, that only soap within the following range for viscosity and pH may be used:

- Viscosity Range (mPa-s or cP): 100 – 2500
- pH Range: 5.5 ~ 6.5


OPERATION

Soap is manually dispensed by depressing push button. Unit is reloaded by unlocking soap tank from wall bracket. Soap will continue to feed properly until empty. Tank supply is replenished manually on cycle determined by maintenance needs.

WARRANTY

One year.

Surface Mounted Soap Surgical Soap Dispenser shall be Model No. 10-0350 as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

