



SPECIFICATION

Recessed Paper Towel Dispenser shall hold and dispense 800 standard multi-fold or 600 standard C-fold paper towels. Towel dispenser door, frame and cabinet shall be fabricated of alloy 18-8 stainless steel, grade 304, 22 gauge. All exposed surfaces shall be No. 4 satin finish and be protected during shipping with a PVC film easily removable after installation. Towel dispensing slot shall have a fully hemmed-in rolled edge for snag-free dispensing and user safety. Door shall be fabricated in double-pan construction with fibreboard filler and shall be attached to cabinet at side with a full length 5mm diameter stainless steel multi-staked piano hinge and be held closed with a tumbler lock keyed alike to other ASI JD MacDonald washroom equipment. Face trim shall be 25mm wide formed from one piece with no mitres, welding or open seams and have 6mm square return to wall. Structural assembly of all components shall be of welded construction.

INSTALLATION

Unit is recessed mounted in wall using No 10. self tapping screws (supplied by others) through concealed mounting holes provided. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use. Rough Wall Opening (RWO) required is 325mm x 670mm x 110mm.


OPERATION

Towels are self-feeding until supply is depleted. Unit may be refilled with a partial load in-place and will continue to feed properly.

WARRANTY

One year.

Recessed Paper Towel Dispenser shall be Model No. 10-0452 as supplied by ASI JD MacDonald.

 All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

