



SPECIFICATION

Recessed Paper Towel Dispenser and Waste Bin shall hold and dispense 800 standard multi-fold or 600 standard C-fold paper towels and shall have a waste capacity of 46 litres. Towel dispenser, door, frame, waste bin and cabinet shall be fabricated of alloy 18-8 stainless steel, grade 304, 22 gauge. All exposed surfaces shall be No. 4 satin finish and be protected during shipment with a PVC film easily removable after installation. Towel dispensing slot shall have a fully hemmed-in rolled edge for snag-free dispensing and user safety. Door shall be fabricated in double-pan construction with fiberboard filler and shall be attached to cabinet at side with a full length 5mm diameter stainless steel multi-staked piano hinge and be held closed with a tumbler lock keyed alike to other ASI JD MacDonald washroom equipment. Waste bin shall have hemmed edges for safety and shall be retained by a tumbler lock keyed alike to other ASI JD MacDonald washroom equipment. Face trim shall be 25mm wide formed from one piece with no mitres, welding or open seams and have 6mm square return to wall. Structural assembly of all components shall be of welded construction. Cabinet shall have no exposed fastening devices or spot welded seams.

INSTALLATION

Unit is mounted in wall recess using four (4) No.10 self tapping screws (supplied by others) through concealed mounting holes provided. For mounting height standards refer to current Building Code of Australia for able bodied and/or disabled use. Note that top of rough wall opening is 19mm below top of unit. Rough Wall Opening (RWO) required is 400mm x 1390mm x 102mm (minimum).

OPERATION

Towels are self-feeding until supply is depleted. Unit may be reloaded with a partial load in-place and will continue to feed properly. Waste bin is emptied manually on cycle determined by maintenance needs. Locked compartment prevents unauthorized access.

WARRANTY

One year.

Recessed Paper Towel Dispenser & Waste Bin shall be Model No. 10-0469 as supplied by ASI JD MacDonald.

All ASI JD MacDonald disabled compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

