



SPECIFICATION

Counter Top Waste Access Door with Waste Bin for counter top installation shall receive 28 litres of solid waste into loose waste bin. Door and face trim shall be fabricated of alloy 18-8 stainless steel, grade 304, 18 gauge. All exposed surfaces shall have No. 4 satin finish and shall be protected during shipment with PVC film easily removable after installation. Face trim shall be one piece construction with no miters or welding. Adjustable stainless steel mounting straps shall accommodate counter thickness from 13mm to 102mm thick. Waste bin shall be provided loose and shall be all welded construction fabricated of corrosion protected steel No. 22 gauge. Downward finger pressure shall open pivoting waste door for disposal of used paper towels into waste bin. Waste door shall return to closed position when pressure is removed.

INSTALLATION

Position unit into appropriate counter top cutout (supplied by others). Installer to bend mounting straps upward to suit counter top thickness. Secure mounting straps to underside of counter top with mounting screws (supplied by others). Counter Top Opening required is 222mm x 318mm.

OPERATION

Waste is inserted through the swinging door by downward pressure. When pressure is released the waste door returns to its closed position. Waste bin is manually emptied on a cycle determined by maintenance needs.

WARRANTY

One year.

Counter Top Waste Access Door with Waste Bin shall be Model No. 10-1003 as supplied by ASI JD MacDonald.

