

TOILET PARTITION HARDWARE



207C

207C Gravity Hinge - Concealed Fix

Specification

Material #304 Stainless Steel
Nylon Inserts
Stainless Steel Snap-on Covers

Finish Satin Stainless Steel

Mounting Screw Fix or Bolt Through

Minimum Hinge Clearance For Lift-Off Hinges 35mm

Specify 207C_LHHC_SS: Left Hand, Hold Closed. Assists door to move towards Hold Closed position
207C_LHHO_SS: Left Hand, Hold Open. Assists door to move towards Hold Open position
207C_RHHC_SS: Right Hand, Hold Closed. Assists door to move towards Hold Closed position
207C_RHHO_SS: Right Hand, Hold Open. Assists door to move towards Hold Open position

Features Gravity assisted door opening/door closing with lift off capability.

Load Rating 15Kg per hinge

For optimum performance -
2 hinges per door up to 30Kgs
For doors over 30Kg allow for 15Kg per hinge

Note: 3 Hinges per door is recommended to prevent door bowing

Note For Bolt Through use 106C_FACEPLATE Concealed Fix Face Plate (Available in Satin Chrome Plate, Bright Chrome Plate and Satin Nickel Plate)

Note: All hinges are available with or without fixings. Please nominate your requirements at the time of ordering .

Related Video [Stainless Steel Cleaning and Maintenance](#)

[Accessibility and safety features of Metlam Australia Toilet Partition Hardware and how to use them](#)

[Troubleshooting your Metlam Australia Toilet Partition Hardware - Hinges](#)

Disclaimer Gravity hinges contain no mechanical components. Functionality of these hinges can vary depending on the environment. When selecting this product, please view our Product Disclosure Statement in the Care and Maintenance Download below.

Downloads & Resources

Care & Maintenance

The photographs and line drawings of the products presented above are representational only.
Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.

