

MODEL 2847A-312

Options:

2847A-312-10 Semi Recessed 2847A-312-11 Surface Mounted

www.bradleyaustralia.com

CONTEMPORARY SERIES MULTI-PURPOSE UNIT 2847A-312



PRODUCT FEATURES:

- Recessed combination 3-in-1 unit:
 Towel dispenser, hand dryer and waste receptacle
- Contemporary design in satin finish stainless steel
- Veco technology eco friendly low electrical consumption
- Low noise (>70dB)
- Large capacity
- 10 year hand dryer replacement warranty

Overall Dimensions 360mm W x 1660mm H x 185mm D



Automatic Hand Dryer Model 220-312

PRODUCT DATA:

CONSTRUCTION:

CABINET: Fabricated of 22 gauge stainless steel with exposed surfaces in 304 (18-8) architectural satin finish. All welded construction with seamless corners and burr-free edges.

DOOR: Fabricated of type 304 (18-8), 18 gauge stainless steel with 13mm return for maximum rigidity. Concealed full length stainless steel piano hinge and two tumbler locks as other Bradley units. TOWEL DISPENSER: Fabricated of type 304 (18-8), 18 gauge stainless steel. All welded construction.

HAND DRYER: Automatic hand dryer Bradley model 220-312. Manufactured of type 304 stainless steel, 2mm thick, featuring vandal resistant key. Motor is brushless high efficiency with low power consumption.

WASTE RECEPTACLE: Fabricated of 22 gauge stainless steel. All welded construction.

CAPACITY:

Towel Dispenser – works well with Bradley Model 2001, 2011 and 2021 paper hand towels.

Waste receptacle - 30 litres.

OPERATION:

Towel dispenser holds paper hand towels without the use of special adaptors. Hand dryer is infrared sensor operated by placing hands into second hole below dryer as indicated. Waste receptacle is large capacity allowing towel to fall to base, alleviating messy washroom.

INSTALLATION:

Recessed unit requires Rough Wall Opening 320mm W \times 1620mm H \times 175mm D (semi-recessed unit only 90mm deep). Set opening minimum 100mm from finished floor.

GUIDE SPECIFICATION:

Recessed combination towel dispenser, hand dryer and waste receptacle shall be fabricated of 18 and 22 gauge stainless steel with exposed surfaces in architectural satin finish.

