TECHNICAL DATA SHEET

RECESSED WASTE RECEPTACLE



MODEL 315-35

- Waste receptacle
- Satin finish stainless steel

Overall Dimensions 356mm W x 1245 H x 190mm D

CONSTRUCTION:

FLANGE: Fabricated of type 304 (18-8) 22 gauge stainless steel with exposed surfaces in architectural satin finish. One piece seamless construction, 25mm wide with 7mm return.

CABINET: Fabricated of type 304 (18-8) 22 gauge stainless steel with exposed surfaces in architectural satin finish. Welded construction with seamless corners and burr-free edges.

DOOR: Fabricated of type 304 (18-8) 18 gauge stainless steel. Warp resistant, with full length piano hinge and tumbler lock keyed as other Newhouse units.

WASTE RECEPTACLE: Fabricated of satin stainless steel.

PUSH FLAP DOOR: Fabricated of type 304 (18-8), 22 gauge stainless steel with exposed surfaces in architectural satin finish. Heavy duty stainless steel piano hinge.

CAPACITY:

34 litres.

OPERATION:

Waste receptacle insert removable by unlocking cabinet door.

INSTALLATION:

Recessed unit requires Rough Wall Opening of $315 \, \text{mm} \ \text{W} \ \text{x} \ 1206 \, \text{mm} \ \text{H} \ \text{x} \ 190 \, \text{mm} \ \text{D}$ (semi-recessed unit only 95 mm deep). Secure to framing with mounting screws (included) at holes provided. Shim at screw points as required.

GUIDE SPECIFICATION:

Recessed waste receptacle shall be fabricated of type 304 (18-8), heavy gauge stainless steel with seamless exposed surfaces in satin finish.

Cabinet door of warp free construction with piano hinge and tumbler lock.

Removable 34 litre stainless steel insert for waste receptacle.

MODEL 315-35

Options:

315-35-10 Semi Recessed 315-35-11 Surface Mounted





