

MODEL 6322

Option:

6322-69 Small Half Litre Bottle

www.bradleyaustralia.com

LIQUID SOAP DISPENSER 6322



PRODUCT FEATURES:

- Plastic globe I litre capacity
- Lavatory mounted
- Top filled
- Spout length 64mm
- Spout length options:6324: 102mm spout6326: 152mm spout

OPTIONAL 38MM SPACER - MODEL P19053
The spacer lifts the plunger spout 38mm
above the counter top to allow additional
clearance over the basin if required

64mm 51mm 021mm 021mm 083mm

PRODUCT DATA:

CONSTRUCTION:

PLUNGER AND SPOUT: Fabricated of type 304 stainless steel.

ESCUTCHEON: Manufactured of heavy chrome plated brass.

SHANK: Manufactured of molded ABS plastic.

VALVE CYLINDER: Manufactured of molded ABS plastic.

VALVE COMPONENTS: Manufactured of Clecon, Buna-N rubber or stainless steel.

PLASTIC GLOBE: Manufactured of translucent polyethylene.

CAPACITY:

I Litre. For optimum performance of use with a 1 litre bottle, we recommend using Bradley soap PB609. If using a system setup to a 5 litre bottle, we recommend using Bradley AM6010 liquid soap. Soap viscosity (thickness) should be less than 100cps (centerpoise).

Ø83mm

OPERATION:

Depress piston for measured amount of liquid soap. Fills from top by unlocking and withdrawing piston and spout assembly using special key provided. The 6322 will work best with Bradley Model PB609 formula liquid soap. Spout is fixed.

INSTALLATION:

Mount dispenser in 25mm diameter hole in lavatory or counter-top. Include dispenser mounting hole location in washroom specifications or mount in unused faucet hole. Shank will accommodate a maximum of 36mm mounting thickness and can be cut in the field.

GUIDE SPECIFICATION:

Lavatory mounted liquid soap dispenser manufactured of type 304 stainless steel, chrome plated brass and molded ABS plastic. Buna-N O-ring seals and duckbills. Valve shall dispense measured amount of Bradley Model PB609 formula liquid soap. Servicing facilitated by use of special wrench.





MODEL 6322

Option:

6322-69 Small Half Litre Bottle

www.bradleyaustralia.com

LIQUID SOAP DISPENSER 6322



PRODUCT FEATURES:

- Plastic globe I litre capacity
- Lavatory mounted
- Top filled
- Spout length 64mm
- Spout length options: 6324: 102mm spout 6326: 152mm spout

OPTIONAL 38MM SPACER - MODEL P19053

The spacer lifts the plunger spout 38mm above the counter top to allow additional clearance over the basin if required

Part 1+2(L): 102mm Spout and Plunger Part 1+2(E): 152mm Spout and Plunger Part 1+2(M): 20mm Spout and Plunger (Wall Mounted) **PARTS BREAKDOWN** Part 14: (0 Spout Tool for Filling Plunger Part 15: Part 20: • White Lock Nut 'O' Ring Part 4: Shank (ABS) Part 3: Chrome Plated Part 4: Part 16: Shank (Brass) Dome Cover Black Thumb Nut Part 5: Duck Bill Valve Part 17: Part 6: Container Cap Part 13: Guide Supply Tube Part 7: Spring Part 18: Rubber Washer Part 8: Duck Bill Valve Part -68(12): Part 19: 1 Litre Bottle Metal Washer Part -67: Part 10: Stainless Steel Bottle SS Collar Part 11: Part 21: Grub Half Litre Bottle Screw Part 9: Valve Body

Part 1+2(S): 64mm Spout and Plunger