

Q50117 - 0120

1


3

1

3

Fold here on door edge ▼










11















A close-up diagram of the door pull assembly. A large black arrow points to the right, indicating the direction to pull the retractable door pull to remove it from the cavity.

Pull the retractable door pull to remove door from cavity.

Latching Passage Set installation (steps 12 - 20)

<p>12</p>  <p>Furniture assembly.</p>	<p>13</p>  <p>Assembly shows both sides interlocking.</p>	<p>14</p>  <p>Internal Furniture Engages with the tailbar from the bolt.</p>	<p>15</p>  <p>Internal Furniture in place.</p>	<p>16</p>  <p>External Furniture Engages with the tabs on the bolt.</p>
<p>17</p>  <p>Fit internal furniture side first.</p>	<p>18</p>  <p>If door is less than 33mm thick use packers. Fit the packers to the inner faces of the furniture, against the door face.</p>	<p>19</p>  <p>Use 25mm Screw Trilobe screw (Thread forming screw)</p>	<p>20</p>  <p>Test bolt with the key, or coin edge in privacy version.</p>	

Strike preparation and installation (steps 21 - 31) Door stop installation (step 32)

<p>21</p>  <p>Partially close door and mark a horizontal line, centre of the latch bolt on the door jamb. Extend horizontal line along the inside face of the door jamb.</p>	<p>22</p>  <p>Mark a vertical line down the door jamb, along the edge of the door.</p>	<p>23</p>  <p>Measure and halve the door thickness.</p>	<p>24</p>  <p>From the vertical line on the door jamb, measure and mark half the door thickness. Draw a second line.</p>	<p>25</p>  <p>Drill Ø25mm hole 20mm deep.</p>
<p>26</p>  <p>Strike basin measures 35mm high.</p>	<p>27</p>  <p>Mark two lines symmetrically either side of the Ø25mm hole centre line.</p>	<p>28</p>  <p>Chisel out basin recess to depth of hole.</p>	<p>29</p>  <p>Fit and mark around strike plate, taking care to keep vertical.</p>	<p>30</p>  <p>Chisel out strike plate recess. Strike plate must be flush with jamb.</p>
<p>31</p>  <p>Drill Ø2mm pilot holes, affix with screws provided.</p>	<p>32</p>  <p>Exterior side of door Door stop</p> <p>A door stop is recommended on the external door face when using a key locking application.</p>			