

MODEL 747

FRAMELESS GLASS MIRROR

PRODUCT FEATURES:

- 6mm surface mounted float glass
 - Highly reflective and durable
 - Surface Mounted
 - Ground and polished edges
 - Mirror glass conforms to AS 1288/2006 Australian Safety Glass Standards
 - Manufactured within the standards to AS/NZ 2208-1996
 - Custom sizing available
 - A Grade Safety Glass
- Overall Dimensions:
Specify "W" width and "H" height. I
- AS 1428.1 compliant sizes below:
450mm x 1000mm
500mm x 1000mm
600mm x 1000mm

OTHER OPTIONS AVAILABLE:

- 1.5mm-10mm Bevel Edge
- Vinyl Backing
- Partial Vinyl Backing



CONSTRUCTION:

MIRROR: Fabricated of first quality 6mm float glass. Layers of the mirror are Float Glass, Sensitizer, Supersensitizer, Silver Layer, Chemical Protection Coat, Paint Base Coat, Paint Top Coat. Edges ground and polished smooth.

Can be used in environments up to 60 degrees celsius.

INSTALLATION:

MODEL 747: Silicone to wall via a full coverage of recommended silicone.

We recommend using a 'non-acidic' or 'neutral cure' silicone similar to Bostic V60.

Option- clip fasteners.

MODEL 747I: Secure mirror to wall via screws holes. Size of screw holes to be advised. To be compliant mirror must be glued and screwed to wall.

GUIDE SPECIFICATION:

Frameless mirror shall be of first quality 6mm float glass.

Full coverage of Silicone is to be applied to the full back of the mirror, it will then be classed as an A Grade Safety

Glass. Mirror must be adhered to a solid surface with recommended silicone.

