


**RP5****FITTING INSTRUCTIONS**

## Door Bottom Seal

**DETAILS****LOCATION**

Bottom of doors, sash windows or around stiles of tilt up doors.

**MIN/MAX GAP**

Up to 15mm (user determined).

**SEAL MATERIAL**

EPDM (black).

**STANDARD FINISH**

Aluminium anodised Satin Clear (Silver) or Bronze.

**USED IN CONJUNCTION**

Raven threshold plates RP13 & RP82.

**DESCRIPTION**

A flexible EPDM weather strip sweep seal that fits to the bottom of doors. It is ideal for screen doors and sash windows to prevent insects from entering up the face of the glass. It is quick and easy to install to the door bottom, being fitted without removing the door. It is also ideal for garage tilt-up doors.

**TOOLS**

RAVEN PRODUCTS PTY. LTD.  
18-22 Aldershot Rd,  
Lonsdale SA 5160 Australia  
T +61 8 8384 5455  
raven.com.au

Raven Products is an  
ISO9001 QMS company  
certified by SGS

Copyright: 06/24 (B)

Designed and produced by  
Raven Products Pty Ltd  
(Australia)

Made in P.R.C. by Raven

Part No. ZSDSRP5


**INSTALLATION****NOTES**

- » The RP5 doorseal may be fitted on the front or back of the door. For inward opening doors check that the floor level is even otherwise seal may jam.

**STEP 1** With door closed, measure the door width.

**STEP 2** Machine cut to measurement.

**STEP 3** Position the seal against the door and screwfix into position. The seal should lightly touch sill.

**FIG.1****PAGE 1 OF 1****FIG.2**