

FIXING	Tiebolt fixing				8
	•	•	•	0	
	Single rear fixing screw	8	8	8	<b>②</b>
BACKSET	Adjustable 60mm - 70mm backset. Spare 127mm backsets available	<b>Ø</b>	<b>Ø</b>	<b>Ø</b>	8
DOOR THICKNESS	Suitable for 35mm - 45mm thick doors	•	•	•	•
PROFILE	Suits Keyline LKW9 (Silca LW4) profile	<b>Ø</b>	8	8	8
CYLINDER	Brass 6 pin cylinder that allows simple rekeying and a medium level of master keying to be accepted	•	8	8	8
SPARES	Special cylinder available with a 5 pin TES5 keyway cylinder (compatible with Gainsborough keys). Code STCYLSS-TES5	•	8	8	8
KEYS	Supplied with two keys per lock	<b>Ø</b>	8	8	8
FINISH	Stainless Steel	<b>O</b>	•	<b>Ø</b>	•
	Polished brass	•	•	•	<b>⊘</b> *
	Chrome plate	•	•	<b>②</b>	<b>⊙</b> *
	Antique bronze	•	8	8	8

<sup>\*</sup> Special order only

DAVCOR Group Pty Ltd ABN. 95 003 562 598 | V.1.0-0207



### **ENTRANCE SET**

#### **Outside function**

Opened by lever when unlocked. Key locks & unlocks both levers.

### **Inside function**

Opened by lever at all times. By operating internal lever in locked position will release outside lever. Internal turnsnib locks and unlocks exterior lever.



# PRIVACY SET

#### **Outside function**

Opened by lever when unlocked. Has an emergency slot in the external handle that unlocks both levers.

### **Inside function**

Opened by lever when unlocked. Internal turnsnib locks or unlocks both levers.



### **PASSAGE SET**

**Outside function** Opened by lever at all times.

## Inside function

Opened by lever at all times.





#### **DUMMY SET Outside function** Pull handle effect only.

# Inside function

As a dummy lever, it is basically used as a non-operational function.

