SEPTONE DEGREASE IT DEGREASER 5L

ITW Polymers & Fluids

Chemwatch Hazard Alert Code: 3

Chemwatch: **5342-55**
Version No: **6.1**
Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Issue Date: **10/03/2023**
Print Date: **29/05/2024**
S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	SEPTONE DEGREASE IT DEGREASER 5L
Chemical Name	Not Applicable
Synonyms	Product Code: ADDI5
Proper shipping name	CORROSIVE LIQUID, N.O.S. (contains sodium hydroxide)
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Vehicle, engine and general purpose degreaser.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	**ITW Polymers & Fluids**	**ITW Polymers & Fluids NZ**
Address	100 Hassall New South Wales 2164 Australia	Unit 2/38 Trugood Drive 2013 New Zealand
Telephone	+61 2 9757 8800	+64 9272 1940
Fax	Not Available	Not Available
Website	Not Available	Not Available
Email	orders@itwpf.com.au	info@aamtech.co.nz

Emergency telephone number

Association / Organisation	**Chemwatch**	**CHEMWATCH EMERGENCY RESPONSE (24/7)**
Emergency telephone numbers	**1800 951 288**	**+61 1800 951 288**
Other emergency telephone numbers	**+61 2 9186 1132**	**+61 3 9573 3188**

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	S5
Classification [1]	Corrosive to Metals Category 1, Skin Corrosion/Irritation Category 1B, Serious Eye Damage/Eye Irritation Category 1, Reproductive Toxicity Category 2
Legend:	***1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI***

Label elements

Hazard pictogram(s)	
Signal word	**Danger**

Hazard statement(s)

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P280	Wear protective gloves, protective clothing, eye protection and face protection.

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.

Precautionary statement(s) Storage

P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1344-09-8	<10	sodium metasilicate
111-76-2	<10	ethylene glycol monobutyl ether
1310-73-2	<1	sodium hydroxide
Not Available	>60	ingredients non-hazardous, including
7732-18-5		water

Legend:	***1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available***

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: ▸ Immediately hold eyelids apart and flush the eye continuously with running water. ▸ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▸ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▸ Transport to hospital or doctor without delay. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: ▸ Immediately flush body and clothes with large amounts of water, using safety shower if available. ▸ Quickly remove all contaminated clothing, including footwear. ▸ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.

	▸ Transport to hospital, or doctor.
Inhalation	▸ If fumes or combustion products are inhaled remove from contaminated area. ▸ Lay patient down. Keep warm and rested. ▸ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▸ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▸ Transport to hospital, or doctor.
Ingestion	▸ For advice, contact a Poisons Information Centre or a doctor at once. ▸ Urgent hospital treatment is likely to be needed. ▸ If swallowed do **NOT** induce vomiting. ▸ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▸ Observe the patient carefully. ▸ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▸ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▸ Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Fire Incompatibility	▸ Reacts with aluminium / zinc producing flammable, explosive hydrogen gas

Advice for firefighters

Fire Fighting	▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ Wear full body protective clothing with breathing apparatus. ▸ Prevent, by any means available, spillage from entering drains or water course. ▸ Use fire fighting procedures suitable for surrounding area.
Fire/Explosion Hazard	▸ Non combustible. ▸ Not considered to be a significant fire risk. ▸ Expansion or decomposition on heating may lead to violent rupture of containers. ▸ Decomposes on heating and may produce toxic fumes of carbon monoxide (CO). Decomposition may produce toxic fumes of: carbon dioxide (CO_2) other pyrolysis products typical of burning organic material.
HAZCHEM	2X

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Slippery when spilt. ▸ Clean up all spills immediately. ▸ Avoid breathing vapours and contact with skin and eyes. ▸ Control personal contact with the substance, by using protective equipment. ▸ Contain and absorb spill with sand, earth, inert material or vermiculite.
Major Spills	Slippery when spilt. ▸ Clear area of personnel and move upwind. ▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ Wear full body protective clothing with breathing apparatus. ▸ Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▸ **DO NOT** allow clothing wet with material to stay in contact with skin ▸ Avoid all personal contact, including inhalation. ▸ Wear protective clothing when risk of exposure occurs. ▸ Use in a well-ventilated area. ▸ Avoid contact with moisture.
Other information	▸ Store in original containers. ▸ Keep containers securely sealed. ▸ Store in a cool, dry, well-ventilated area. ▸ Store away from incompatible materials and foodstuff containers.

Conditions for safe storage, including any incompatibilities

Suitable container	▸ Lined metal can, lined metal pail/ can. ▸ Plastic pail. ▸ Polyliner drum. ▸ Packing as recommended by manufacturer.
Storage incompatibility	▸ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	ethylene glycol monobutyl ether	2-Butoxyethanol	20 ppm / 96.9 mg/m3	242 mg/m3 / 50 ppm	Not Available	Not Available
Australia Exposure Standards	sodium hydroxide	Sodium hydroxide	Not Available	Not Available	2 mg/m3	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
sodium metasilicate	5.9 mg/m3	65 mg/m3	390 mg/m3
ethylene glycol monobutyl ether	60 ppm	120 ppm	700 ppm
sodium hydroxide	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
sodium metasilicate	Not Available	Not Available
ethylene glycol monobutyl ether	700 ppm	Not Available
sodium hydroxide	10 mg/m3	Not Available
water	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
sodium metasilicate	E	≤ 0.01 mg/m³
Notes:	***Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.***	

Exposure controls

Appropriate engineering controls	Use in a well-ventilated area General exhaust is adequate under normal operating conditions.
Individual protection measures, such as personal protective equipment	
Eye and face protection	▸ Safety glasses with side shields; or as required, ▸ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]

	‣ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.
Skin protection	See Hand protection below
Hands/feet protection	Wear chemical protective gloves, e.g. PVC. Wear safety footwear.
Body protection	See Other protection below
Other protection	‣ Overalls. ‣ P.V.C apron. ‣ Barrier cream. ‣ Skin cleansing cream.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	@1@-AUS / Class1 @2@	-
up to 50	1000	-	@1@-AUS / Class 1 @2@
up to 50	5000	Airline *	-
up to 100	5000	-	@1@-2 @2@
up to 100	10000	-	@1@-3 @2@
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Salmon pink, slightly viscous, alkaline liquid with a distinctive solvent odour; mixes with water. pH ~12.7

Physical state	Liquid	**Relative density (Water = 1)**	1.06
Odour	Not Available	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Applicable
pH (as supplied)	Alkaline	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (cSt)**	Not Available
Initial boiling point and boiling range (°C)	Not Available	**Molecular weight (g/mol)**	Not Applicable
Flash point (°C)	Not Applicable	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	Not Applicable	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	Not Applicable	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	Not Applicable	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Miscible	**pH as a solution (1%)**	Not Available

Vapour density (Air = 1)	Not Available	**VOC g/L**	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▸ Unstable in the presence of incompatible materials. ▸ Product is considered stable. ▸ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Not normally a hazard due to non-volatile nature of product
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Ingestion may result in nausea, abdominal irritation, pain and vomiting
Skin Contact	Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. The material can produce severe chemical burns following direct contact with the skin. The material may accentuate any pre-existing skin condition Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	If applied to the eyes, this material causes severe eye damage.
Chronic	Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

SEPTONE DEGREASE IT DEGREASER 5L	**TOXICITY**	**IRRITATION**
	Not Available	Not Available
sodium metasilicate	**TOXICITY**	**IRRITATION**
	dermal (rat) LD50: >5000 mg/kg[1]	Skin (human): 250 mg/24h SEVERE
	Inhalation (Rat) LC50: >2.06 mg/l4h[1]	Skin (rabbit): 250 mg/24h SEVERE
	Oral (Rat) LD50: 1153 mg/kg[2]	
ethylene glycol monobutyl ether	**TOXICITY**	**IRRITATION**
	Dermal (Guinea Pig) LD50: 210 mg/kg[2]	Eye (rabbit): 100 mg SEVERE * [Union Carbide]
	Inhalation (Rat) LC50: 450 ppm4h[2]	Eye (rabbit): 100 mg/24h-moderate
	Oral (Rat) LD50: 250 mg/kg[2]	Eye: adverse effect observed (irritating)[1]
		Skin (rabbit): 500 mg, open; mild
		Skin: adverse effect observed (irritating)[1]
		Skin: no adverse effect observed (not irritating)[1]
sodium hydroxide	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: 1350 mg/kg[2]	Eye (rabbit): 0.05 mg/24h SEVERE
	Oral (Rabbit) LD50; 325 mg/kg[1]	Eye (rabbit):1 mg/24h SEVERE
		Eye (rabbit):1 mg/30s rinsed-SEVERE
		Eye: adverse effect observed (irritating)[1]
		Skin (rabbit): 500 mg/24h SEVERE
		Skin: adverse effect observed (corrosive)[1]
water	**TOXICITY**	**IRRITATION**
	Oral (Rat) LD50: >90000 mg/kg[2]	Not Available

Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***

SODIUM METASILICATE	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
ETHYLENE GLYCOL MONOBUTYL ETHER	NOTE: Changes in kidney, liver, spleen and lungs are observed in animals exposed to high concentrations of this substance by all routes. ** ASCC (NZ) SDS For ethylene glycol monoalkyl ethers and their acetates (EGMAEs): Typical members of this category are ethylene glycol propylene ether (EGPE), ethylene glycol butyl ether (EGBE) and ethylene glycol hexyl ether (EGHE) and their acetates. EGMAEs are substrates for alcohol dehydrogenase isozyme ADH-3, which catalyzes the conversion of their terminal alcohols to aldehydes (which are transient metabolites). Further, rapid conversion of the aldehydes by aldehyde dehydrogenase produces alkoxyacetic acids, which are the predominant urinary metabolites of mono substituted glycol ethers. **Acute Toxicity:** Oral LD50 values in rats for all category members range from 739 (EGHE) to 3089 mg/kg bw (EGPE), with values increasing with decreasing molecular weight. Four to six hour acute inhalation toxicity studies were conducted for these chemicals in rats at the highest vapour concentrations practically achievable. Values range from LC0 > 85 ppm (508 mg/m3) for EGHE, LC50 > 400ppm (2620 mg/m3) for EGBEA to LC50 > 2132 ppm (9061 mg/m3) for EGPE. Animal testing showed that exposure to ethylene glycol monobutyl ether resulted in toxicity to both the mother and the embryo. Reproductive effects were thought to be less than that of other monoalkyl ethers of ethylene glycol. Chronic exposure may cause anaemia, with enlargement and fragility of red blood cells. It is thought that in animals butoxyethanol may cause generalized clotting and bone infarction. In animals, 2-butoxyethanol also increased the rate of some cancers, including liver cancer.
SODIUM HYDROXIDE	The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.
WATER	No significant acute toxicological data identified in literature search.
SODIUM METASILICATE & ETHYLENE GLYCOL MONOBUTYL ETHER	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
SODIUM METASILICATE & SODIUM HYDROXIDE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.
ETHYLENE GLYCOL MONOBUTYL ETHER & SODIUM HYDROXIDE	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✓	**Reproductivity**	✓
Serious Eye Damage/Irritation	✓	**STOT - Single Exposure**	✗
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✗

Legend: ✗ ***– Data either not available or does not fill the criteria for classification***
✓ ***– Data available to make classification***

SECTION 12 Ecological information

Toxicity

SEPTONE DEGREASE IT DEGREASER 5L

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

sodium metasilicate

Endpoint	Test Duration (hr)	Species	Value	Source
LC50	96h	Fish	260-310mg/l	2
EC50	72h	Algae or other aquatic plants	207mg/l	2
EC50	48h	Crustacea	0.28-0.57mg/l	4
EC50(ECx)	48h	Crustacea	0.28-0.57mg/l	4

ethylene glycol monobutyl ether	**Endpoint**	**Test Duration (hr)**	**Species**	**Value**	**Source**
	LC50	96h	Fish	1700mg/l	Not Available
	EC50	48h	Crustacea	164mg/l	2
	EC50	72h	Algae or other aquatic plants	623mg/l	2
	EC10(ECx)	48h	Crustacea	7.2mg/l	2
	EC50	96h	Algae or other aquatic plants	720mg/l	2
sodium hydroxide	**Endpoint**	**Test Duration (hr)**	**Species**	**Value**	**Source**
	LC50	96h	Fish	144-267mg/l	4
	EC50	48h	Crustacea	34.59-47.13mg/l	4
	EC50(ECx)	48h	Crustacea	34.59-47.13mg/l	4
water	**Endpoint**	**Test Duration (hr)**	**Species**	**Value**	**Source**
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data***				

Prevent, by any means available, spillage from entering drains or water courses.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol monobutyl ether	LOW (Half-life = 56 days)	LOW (Half-life = 1.37 days)
sodium hydroxide	LOW	LOW
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
ethylene glycol monobutyl ether	LOW (BCF = 2.51)
sodium hydroxide	LOW (LogKOW = -3.8796)

Mobility in soil

Ingredient	Mobility
ethylene glycol monobutyl ether	HIGH (Log KOC = 1)
sodium hydroxide	LOW (Log KOC = 14.3)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	▸ Recycle wherever possible. ▸ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. ▸ Treat and neutralise at an approved treatment plant. ▸ Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO
HAZCHEM	2X

Land transport (ADG)

14.1. **UN number or ID number**	1760
14.2. **UN proper shipping name**	CORROSIVE LIQUID, N.O.S. (contains sodium hydroxide)
14.3. **Transport hazard class(es)**	Class: 8 Subsidiary Hazard: Not Applicable
14.4. **Packing group**	III
14.5. **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	Special provisions: 223 274 Limited quantity: 5 L

Air transport (ICAO-IATA / DGR)

14.1. **UN number**	1760
14.2. **UN proper shipping name**	Corrosive liquid, n.o.s. * (contains sodium hydroxide)
14.3. **Transport hazard class(es)**	ICAO/IATA Class: 8 ICAO / IATA Subsidiary Hazard: Not Applicable ERG Code: 8L
14.4. **Packing group**	III
14.5. **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	Special provisions: A3 A803 Cargo Only Packing Instructions: 856 Cargo Only Maximum Qty / Pack: 60 L Passenger and Cargo Packing Instructions: 852 Passenger and Cargo Maximum Qty / Pack: 5 L Passenger and Cargo Limited Quantity Packing Instructions: Y841 Passenger and Cargo Limited Maximum Qty / Pack: 1 L

Sea transport (IMDG-Code / GGVSee)

14.1. **UN number**	1760
14.2. **UN proper shipping name**	CORROSIVE LIQUID, N.O.S. (contains sodium hydroxide)
14.3. **Transport hazard class(es)**	IMDG Class: 8 IMDG Subsidiary Hazard: Not Applicable
14.4. **Packing group**	III
14.5 **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	EMS Number: F-A , S-B Special provisions: 223 274 Limited Quantities: 5 L

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
sodium metasilicate	Not Available
ethylene glycol monobutyl ether	Not Available
sodium hydroxide	Not Available
water	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
sodium metasilicate	Not Available
ethylene glycol monobutyl ether	Not Available
sodium hydroxide	Not Available
water	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

sodium metasilicate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
Australian Inventory of Industrial Chemicals (AIIC)

ethylene glycol monobutyl ether is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
Australian Inventory of Industrial Chemicals (AIIC)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

sodium hydroxide is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
Australian Inventory of Industrial Chemicals (AIIC)

water is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (sodium metasilicate; ethylene glycol monobutyl ether; sodium hydroxide; water)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes

National Inventory	Status
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 Other information

Revision Date	10/03/2023
Initial Date	20/02/2019

SDS Version Summary

Version	Date of Update	Sections Updated
5.1	10/12/2021	Classification change due to full database hazard calculation/update.
6.1	10/03/2023	Classification change due to full database hazard calculation/update.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.
Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
TEL (+61 3) 9572 4700.