

THE ECONOMIC 3D MEASURING SOLUTION



MEASURING ARM BACES 6 AXES

The Baces measuring arm has an internal calibration ensured by an aluminium and carbon fiber mechanical structure, making it extremely lightweight and stable.

PRODUCT ADVANTAGE

Baces arm is an entry level solution used for most of measuring application. It has a good quality for its value.

Its lightness allows to probe longer and without effort.

Temperature compensation

The Baces arm is a portable solution which is used either in metrological department or in the workshop. The temperature probes fit the measurements in reference to temperature variations.

Compatible software: Metrolog, Polyworks, Geomagic, Powerinspect, Capps, etc.



TECHNICAL SPECIFICATIONS

			Probing performances*	
SERIE 100 CARBON	Arm model	Working volume	Single point repeatability	Volumetric accuracy
	М	2.6 m	0.028 mm	0.044 mm
	G	3.2 m	0.045 mm	0.064 mm
	XG	4.2 m	0.072 mm	0.097 mm
	XL	4.6 m	0.094 mm	0.120 mm
SERIE 200 ALUMINUM	М	2.6 m	0.040 mm	0.065mm
	G	3.2 m	0.068 mm	0.095 mm
	XG	4.2 m	0.098 mm	0.210 mm
	XL	4.6 m	0.120 mm	0.350 mm

All specifications are subject to change without notification

The Baces arm is available in series 100 (more accurate, with carbon fiber tubes) and series 200 (more competitive, with aluminium tubes).

HARDWARE SPECIFICATIONS

Operating temperature range: 10-45 °C Power supply: universal worldwide voltage 100-250V Humidity: 95%, non condensing - IP51



^{*} According to ASME B89 4.22