EM5700 SERIES

Single Door Monitored & Non Monitored

EM5700 DESCRIPTION

The **LOX EM5700** Series product line is a comprehensive Electro Magnetic Lock range with up to **580kg** holding force. It is one of the most reliable and most successful Electro Magnetic Locks in the Australian market in this product category.

THE MONITORED MAGNETIC LOCKS HAVE:

- A built-in Hall Effect Sensor for monitoring the lock/ unlock status of the locking device
 (LSS – Lock Status Sensor)
- A built-in reed switch contact for monitoring the open/closed status of the door
 (DSS – Door Status Sensor)
- Highly visible red/green LED Status Light
- Anti-Tamper-Fixing-Plate (with monitored version) to avoid hostile attacks targeted on the dome-nut-fixing bolt of the Armature Plate



EM5700	SINGLE ELECTRO MAGNETIC LOCK NON MONITORED
EM5700M	SINGLE ELECTRO MAGNETIC LOCK MONITORED
HOLDING STRENGTH	UP TO 580KG, TESTED TO 1 MILLION CYCLES
VOLTAGE/CURRENT	DUAL VOLTAGE 12/24VDC 12VDC = 500mA 24VDC = 260mA
APPROVALS	UP TO 4 HOUR FIRE RATED TO A.S STANDARD, CE & C-TICK 🥻 💰
LSS MONITORING	LSS LOCK STATUS SENSOR (HALL EFFECT)
DSS MONITORING	DOOR STATUS SENSOR (REED SWITCH)
LED LIGHT STATUS	LED LIGHT STATUS INDICATES LOCKED OR UNLOCKED STATUS
ENVIRONMENTAL	OPERATIONAL TEMPERATURE RANGE - 20 DEG. C TO 60 DEG. C.






EM5700 SERIES

Single Door Monitored & Non Monitored

PRODUCT DIMENSIONS



ACCESSORIES



EM5700MP

LOX MOUNTING PLATE FOR EM5700/M



AMGB1-12

LOX U SHAPE ARMATURE HOLDER FOR GLASS DOORS SUITS EM5700 NON MONITORED

AMGB1-12-DSS

LOX U SHAPE ARMATURE HOLDER FOR GLASS DOORS SUITS EM5700M MONITORED



AMZB1-LP

LOX L & Z BRACKET FOR INWARDS OPENING DOORS SUITS FM5700

AMZB1-LP-DSS

LOX L & Z BRACKET FOR INWARDS OPENING DOORS SUITS EM5700M



AMAB1

LOX ARMATURE HOLDER AND DRESS PLATE FOR GLASS DOORS SUITS EM5700

AMAB1-DSS

LOX ARMATURE HOLDER AND DRESS PLATE FOR GLASS DOORS SUITS EM5700M



AMFB1

LOX L BRACKET FOR SUITS EM5700 SERIES

AMLB1

LOX ADJUSTABLE L BRACKET SUITS EM5700 SERIES

