\mathbf{X}

Baseline product line

MotionProtect Outdoor Jeweller

Wireless outdoor motion detector with an anti-masking and pet-immunity



2

GRADE

EN 50131

PD 6662

2017

UL®

LISTED

IP55



- From 3 to 15 m adjustable detection distance
- LISA and SmartDetect software algorithms to filter false alarms
- Temperature compensation for effective detection in heat and cold
- Pet immunity to animals with height up to 80 cm



- The system controls each device state and reports if there is a malfunction or connection loss
- Automatic detector self-diagnosis with state reporting to the hub
- Instant maintenance notifications





- Up to 1,700 m of radio communication in an open space and twice as much with a range extender
- Data is encrypted throughout the transmission process
- Regular polling of each system device to display current statuses in apps
- Up to 5 years of operation with pre-installed batteries
- In-app low battery warning
- Replaceable CR123A batteries
- Optional 12 V == power supply connection with pre-installed batteries as a backup power source

Sabotage resistance 5

- Intelligent anti-masking system
- Tamper alarm
- Holding screw to secure the device on SmartBracket



- Pairing with a hub via QR code
- SmartBracket panel to mount the device without disassembling the enclosure

Device authentication against spoofing

- Hood to protect sensors from rain and snow (sold separately)
- Remote control and configuration in Ajax apps

Superior, Fibra, and Baseline product lines are mutually compatible. This opens up numerous possibilities for building systems of any configuration.

Compliance

EN 50131 (Grade 2) PD 6662:2017 UL369, ULC S306

Compatibility

Hubs

Hub Jeweller, Hub Plus Jeweller, Hub 2 (2G) Jeweller, Hub 2 (4G) Jeweller, Hub 2 Plus Jeweller, Hub Hybrid (2G), Hub Hybrid (4G)

Range extenders ReX Jeweller, ReX 2 Jeweller

Communication with a hub

Jeweller communication technology

Communication range up to 1,300 m In an open space

Radio frequency band

Detection

Sensing elements 2 × PIR sensor

Motion detection distance 3–15 m Adjusted using a scrollbar on the detector's back

		866.0-866.5 MHz 868.0-868.6 MHz 868.7-869.2 MHz 905.0-926.5 MHz 915.85-926.5 MHz 921.0-922.0 MHz Depends on the sales region	Detection angles horizontal — 90° vertical — N/A Sensitivity 3 levels Adjusted by PRO or user with admin rights in the Ajax app Pet immunity height: up to 80 cm weight: N/A
Power supply	Installation	Enclosure	Complete set
Battery	Recommended installation height	Colour	MotionProtect Outdoor Jeweller
2 × CR123A	from 0.8 to 1.3 m	white	SmartBracket mounting panel
Pre-installed			2 × CR123A battery (pre-installed)
	Operating temperature range	Dimensions	Installation kit
External power supply	from -25°C to +65°C	183 × 70 × 65 mm	Quick start guide

5–28 V=, 200 mA 12 V= power supply is recommended to use	Operating humidity up to 95%	Weight 322 g	
		Protection class IP55	



For detailed information, scan the QR code or follow the link:

ajax.systems/support/devices/motionprotect-outdoor/

support@ajax.systems

@AjaxSystemsSupport_Bot

