

PA-A4-12DC-4A4 Battery Back up

4 amp 4 Channel CCTV Power Supply



Features

- Dual 7AH Battery Back- Up option
- 4 Individually Fused Channels
- Short Circuit, Over Load and High
- Temperature Protection
- Low Ripple Voltage <40mV
- AC Power Indicator on Front Cover
- Individual LED's for each output
- External Power on / off switch
- Power Cable Supplied-
- No hard wiring
- Strong metal cabinet with rear cable access
- and punch outs for easy installation
- 2 Year Warranty

Specification

MODEL	PA-A4-12DC-4A4 Battery Back up
Number of Channels	4
Output Voltage	Variable 12 - 14VDC + 10%
Total Output Current	4A (0-1.6A / Channel MAX)
PTC Fuse Rating	1.6A 30V
Battery Back - Up	Max 2 x 7 Ah SLA Battery
General Protection	Each Output has a PTC fuse with LED indicator.
Circuit Short Protection	When a short circuit occurs, the Individual PTC Fuse will go on Circuit. When the short is removed, the PTC fuse will automatically reset.
Operating Temperature	Minus 10 - 40°C maximum
Humidity	20-90% RH
Input Voltage	240VAC @ 50Hz
Output Fuse Rating	SMPSU - 3A
LED Status Indicator	Green - Not in use Blue - In use Amber - 80 % of capacity Red - Short circuit
Approvals	Ctick, EMC, AS/NZS 60950-1-2003 AS/NZS CISPR 22:2006
Dimension (mm)	230H X 280W X 82D