in accordance with HSNO



Distributor in New Zealand:

33 Ha Crescent, Wiri, Auckland

+64 9 25000 92

sales@mipa.nz

www.mipa.nz

Mipa New Zealand

2104 New Zealand

Phone: +64 9 25000 91

Revision: 23.01.2018

Printing date 15.02.2021

Version number 92

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: BC-Lack-Fertigton
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0

Fax.: +49(0)8703-922-100

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

24hr Emergency Assistance in New Zealand National Poison Control Centre: 0800 POISON [764 766]

Fax:

Web:

Fmail:

· Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

2 Hazards identification

Classification of the substance or mixture



flame

H226 Flammable liquid and vapour. Flam. Liq. 3



H315 Causes skin irritation. Skin Irrit. 2

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Acute Tox. 5 H333 May be harmful if inhaled.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Xylene

ethylbenzene

· Hazard statements

H226 Flammable liquid and vapour.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

in accordance with HSNO



Revision: 23.01.2018

Printing date 15.02.2021 Version number 92

Trade name: BC-Lack-Fertigton

(Contd. of page 1)

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous	components:	
123-86-4	n-Butyl acetate	50-100%
	🊸 Flam. Liq. 3, H226; ∳ STOT SE 3, H336	
1330-20-7		5-<10%
	Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
78-93-3	Methyl ethyl ketone	2.5-<10%
	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336; Acute Tox. 5, H303; Acute Tox. 5, H313	
64742-95-6	Hydrocarbons, C9, aromatics	5-<10%
	 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336; Acute Tox. 5, H303; Acute Tox. 5, H313 	
108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%
	🊸 Flam. Liq. 3, H226; 伙 STOT SE 3, H336; Acute Tox. 5, H333	
100-41-4	ethylbenzene	<2.5%
	Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Acute Tox. 5, H303; Aquatic Chronic 3, H412	
85711-46-2	Fatty acids, C14-18 and C16-18-unsatd., maleated	≥0.1-<1%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317	
Additional i	information: For the wording of the listed hazard phrases refer to section 16	

4 First aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Generally the product does not irritate the skin.

Immediately rinse with water.

(Contd. on page 3)

in accordance with HSNO



Revision: 23.01.2018

Printing date 15.02.2021 Version number 92

Trade name: BC-Lack-Fertigton

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

ΝZ

in accordance with HSNO



Printing date 15.02.2021 Version number 92 Revision: 23.01.2018

Trade name: BC-Lack-Fertigton

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

Ingredients with lim	nit values that require monitoring at the workplace:		
123-86-4 n-Butyl acetate			
•	Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm		
IOELV (EU)	Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm		
1330-20-7 Xylene			
WES (New Zealand)	Long-term value: 217 mg/m³, 50 ppm		
IOELV (EU)	Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin		
78-93-3 Methyl ethyl ketone			
WES (New Zealand)	Short-term value: 890 mg/m³, 300 ppm Long-term value: 445 mg/m³, 150 ppm bio		
IOELV (EU)	Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm		
108-65-6 2-Methoxy	-1-methylethyl acetate		
IOELV (EU)	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin		
100-41-4 ethylbenze	100-41-4 ethylbenzene		
WES (New Zealand)	Short-term value: 543 mg/m³, 125 ppm Long-term value: 434 mg/m³, 100 ppm		
IOELV (EU)	Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin		

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

in accordance with HSNO



(Contd. of page 4)

Printing date 15.02.2021 Version number 92 Revision: 23.01.2018

Trade name: BC-Lack-Fertigton

· Protection of hands:



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Breakthrough time of glove material Value for the permeation: Level ≤ 1
- Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 79-80.5 °C

• Flash point: 23 °C (DIN 53213)

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 370 °C (DIN 51794)

· **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 7.5 Vol %

· Vapour pressure at 20 °C: 105 hPa

Density at 20 °C: 0.984 g/cm³ (DIN 53217)

(Contd. on page 6)

in accordance with HSNO



Printing date 15.02.2021 Version number 92 Revision: 23.01.2018

Trade name: BC-Lack-Fertigton

	(Contd. of page
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	130-140 s (DIN 53211/4)
· Solvent content:	
VOC (EC)	74.60 %
Solids content (weight-%):	25.4 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 v	· LD/LC50 values relevant for classification:			
123-86-4 r	123-86-4 n-Butyl acetate			
Oral	LD50	13,100 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
1330-20-7	1330-20-7 Xylene			
Oral	LD50	5,251 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	29 mg/l (rat)		
64742-95-	64742-95-6 Hydrocarbons, C9, aromatics			
Oral	LD50	>2,000 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rabbit)		

- · Primary irritant effect:
- Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Irritating effect.
- Respiratory or skin sensitisation No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

(Contd. on page 7)

in accordance with HSNO



Revision: 23.01.2018

Printing date 15.02.2021 Version number 92

Trade name: BC-Lack-Fertigton

(Contd. of page 6)

12 Ecological information

· Toxicity

Irritant

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN	N-Num	ber
------	-------	-----

· ADR, IMDG, IATA UN1263

· UN proper shipping name

· **ADR** UN1263 PAINT

· **IMDG, IATA** PAINT

· Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.

(Contd. on page 8)

in accordance with HSNO Version number 92



Revision: 23.01.2018

Printing date 15.02.2021

Trade name: BC-Lack-Fertigton

(Contd. of page 7) ·Label · IMDG, IATA 3 Flammable liquids. · Class · Label · Packing group ADR, IMDG, IATA III· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 30 · EMS Number: F-E,<u>S-E</u> · Stowage Category Α · Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · Transport category 3 Tunnel restriction code D/E · Remarks: ≤ 450 I: 2.2.3.1.5 ADR ·IMDG · Limited quantities (LQ) 5L · Remarks: ≤ 5 *I*: 2.2.3.1.5 *IMDG* · UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· HSNO Approval numbers		
	n-Butyl acetate	HSR001091
1330-20-7	Xylene	HSR000983
78-93-3	Methyl ethyl ketone	HSR001190
	Hydrocarbons, C9, aromatics	HSR001503
108-65-6	2-Methoxy-1-methylethyl acetate	HSR001219
100-41-4	ethylbenzene	HSR001151

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





NEW ZEALAND

Class 3.1C Flammable Liquid & Vapour Class 6.1E Inhalation Hazard Class 6.3A Skin Irritant

Class 6.4A Eye Irritant

Class 6.9B Transient Narcotic Effect Class 9.1C Aquatic Toxicity

(Contd. on page 9)

HSR002662 Surface Coatings & Colourants (Flammable)

in accordance with HSNO



Printing date 15.02.2021 Version number 92 Revision: 23.01.2018

Trade name: BC-Lack-Fertigton

(Contd. of page 8)

· Signal word Warning

· Hazard-determining components of labelling:

Xylene

ethylbenzene

· Hazard statements

H226 Flammable liquid and vapour.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

Other regulations, limitations and prohibitive regulations

Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Approval Number: The HSNO Approval Number for this Group Standard is HSR002662. Refer also to the Site & Storage requirements document.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

(Contd. on page 10)

in accordance with HSNO



Printing date 15.02.2021 Version number 92 Revision: 23.01.2018

Trade name: BC-Lack-Fertigton

(Contd. of page 9)

H332 Harmful if inhaled.

H333 May be harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Contact:

· Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 5: Acute toxicity – Category 5

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

NZ