

CRC (NZ) 5087 Brakleen Blaster Aerosol CRC Industries (CRC Industries New Zealand)

Chemwatch Hazard Alert Code: 3

Chemwatch: 21-8162 Version No: 6.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: **10/12/2021** Print Date: **19/01/2022** S.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	CRC (NZ) 5087 Brakleen Blaster Aerosol
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Degreasing brake parts. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Application is by spray atomisation from a hand held aerosol pack

Details of the supplier of the safety data sheet

Registered company name	CRC Industries (CRC Industries New Zealand)		
Address	10 Highbrook Drive East Tamaki Auckland New Zealand		
Telephone	+64 9 272 2700		
Fax	+64 9 274 9696		
Website	www.crc.co.nz		
Email	customerservices@crc.co.nz		

Emergency telephone number


Association / Organisation	CRC Industries (CRC Industries New Zealand)	CHEMWATCH EMERGENCY RESPONSE	
Emergency telephone numbers	NZ Poisons Centre 0800 POISON (0800 764 766)	+64 800 700 112	
Other emergency telephone numbers	111 (NZ Emergency Services)	+61 2 9186 1132	

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification ^[1]	Aerosols Category 1, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Carcinogenicity Category 2, Specific Target Organ Toxicity - Single Exposure Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 1, Hazardous to Soil Organisms, Hazardous to Terrestrial Vertebrates
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	2.1.2A, 6.1D (oral), 6.3A, 6.4A, 6.7B, 6.9B, 9.1A, 9.2C, 9.3B





Signal word Danger

Hazard statement(s)

H222+H229	Extremely flammable aerosol. Pressurized container: may burst if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H423	Hazardous to soil organisms.
H432	Hazardous to terrestrial vertebrates.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor/physician/first aider.
P314	Get medical advice/attention if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
127-18-4	20-40	perchloroethylene
75-09-2	5-20	methylene chloride
142-82-5	20-40	heptane
124-38-9	1-9	carbon dioxide
Not Available		NOTE: Manufacturer has supplied full ingredient
Not Available		information to allow CHEMWATCH assessment.
Legend: 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

SECTION 4 First aid measures

Eye Contact	 If aerosols come in contact with the eyes: Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If solids or aerosol mists are deposited upon the skin: Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation.
Inhalation	 If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 Avoid giving milk or oils. Avoid giving alcohol. Not considered a normal route of entry. If poisoning occurs, contact a doctor or Poisons Information Centre.

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

for intoxication due to Freons/ Halons;

A: Emergency and Supportive Measures

- Maintain an open airway and assist ventilation if necessary
- Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- Monitor the ECG for 4-6 hours
- B: Specific drugs and antidotes:
- There is no specific antidote
- C: Decontamination
- Inhalation; remove victim from exposure, and give supplemental oxygen if available.
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. DO NOT induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes)
- D: Enhanced elimination:
- * There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal.

POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition

- + Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability.
- No specific antidote.
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- If lavage is performed, suggest endotracheal and/or esophageal control.
- Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- Treatment based on judgment of the physician in response to reactions of the patient

Treat symptomatically.

For acute or short term repeated exposures to perchloroethylene:

Tetrachloroethylene / perchloroethylene is well absorbed through the lungs with peak levels more important than duration in determining blood concentration. Lungs excrete most of the absorbed tetrachloroethylene in an unchanged state; about 3% is converted by the liver to form trichloracetic acid and subsequently excreted by the kidney. Exhaled material has a biological half-life of 65 hours.

INHALATION:

The treatment of acute inhalation exposures is supportive with initial attention directed to evaluation / support of ventilation and circulation. As with all hydrocarbons care must be taken to reduce the risk of aspiration by proper positioning and medical observation.

INGESTION:

+ The ingestion level at which emesis should be induced is difficult to predict in the absence of extensive human studies.

The role of charcoal and cathartics remains uncertain.

[Ellenhorn and Barceloux: Medical Toxicology] BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collect	ted from a healthy w	worker who has been exposed at the Exposure	e Standard (ES or TLV):	
Determinant	Index	Sampling Time	Comments	
1. Perchloroethylene in end-exhaled air	10 ppm	Prior to last shift of work-week		
2. Perchloroethylene in blood	1 mg/L	Prior to last shift of work-week		
3. Trichloroacetic acid in urine	7 mg/L	End of work-week	NS, SQ	
NC: Non anacific determinants also each offer avacques to other materials				

NS: Non-specific determinant; also seen after exposure to other materials

SQ: Semi-quantitative determinant - Interpretation may be ambiguous; should be used as a screening test or confirmatory test.

SECTION 5 Firefighting measures

Extinguishing media

SMALL FIRE:

Water spray, dry chemical or CO2

LARGE FIRE:

Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	 Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark. Combustion products include: carbon dioxide (CO2) carbon monoxide (CO) hydrogen chloride phosgene other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. May emit clouds of acrid smoke

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation.
Major Spills	 Remove leaking cylinders to a safe place if possible. Release pressure under safe, controlled conditions by opening the valve. DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. 	

Other information	 Store below 38 deg. C. Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can Store in original containers in approved flammable liquid storage area. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. No smoking, naked lights, heat or ignition sources.
	Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container	 DO NOT use aluminium or galvanised containers Aerosol dispenser. Check that containers are clearly labelled.
Storage incompatibility	 Haloalkenes are highly reactive. Some of the more lightly substituted lower members are highly flammable; many members of the group are peroxidisable and polymerisable. Avoid reaction or contact with potassium or its alloys - although apparently stable on contact with a wide rage of halocarbons, reaction products may be shock-sensitive and may explode with great violence on light impact. Severity generally increases with the degree of halocarbon substitution and potassium-sodium alloys give extremely sensitive mixtures. Tetrachloroethylene: decomposes slowly in contact with water or moisture forming trichloroacetic acid and hydrochloric acid reacts violently with concentrated nitric acid (producing carbon dioxide), strong oxidisers, strong alkalis, powdered chemically active metals such as aluminium, barium, beryllium, lithium, zinc is incompatible with nitrogen tetroxide, finely divided metals decomposes in UV light, on contact with red-hot metals, and at temperatures above 150 C, releasing hydrogen chloride, carbon monoxide and phosgene corrodes metals in the presence of moisture can oxidise in presence of air and light. The presence of 0.5% trichloroethylene as an impurity caused generation of dichloroacetylene during unheated drying over solid sodium hydroxide. Subsequent fractional distillation produced an explosion. Segregate from alcohol, water.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	perchloroethylene	Perchloroethylene (Tetrachloroethylene)	20 ppm / 136 mg/m3	271 mg/m3 / 40 ppm	Not Available	skin-Skin absorption 6.7A-Confirmed carcinogen
New Zealand Workplace Exposure Standards (WES)	methylene chloride	Methylene chloride (Dichloromethane)	50 ppm / 174 mg/m3	Not Available	Not Available	6.7B-Suspected carcinogen
New Zealand Workplace Exposure Standards (WES)	heptane	Heptane (n-Heptane)	400 ppm / 1640 mg/m3	2050 mg/m3 / 500 ppm	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	carbon dioxide	Carbon dioxide	5000 ppm / 9000 mg/m3	54000 mg/m3 / 30000 ppm	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
perchloroethylene	Not Available	Not Available		Not Available
methylene chloride	Not Available	Not Available		Not Available
heptane	500 ppm	830 ppm		5000* ppm
Ingredient	Original IDLH		Revised IDLH	
perchloroethylene	150 ppm		Not Available	
methylene chloride	2,300 ppm		Not Available	
heptane	750 ppm		Not Available	
carbon dioxide	40,000 ppm		Not Available	

Exposure controls

	CARE: Use of a quantity of this material in confined space or poorly ventilated area, where rapid build up of concentrated atmosphere may occur, could require increased ventilation and/or protective gear					
Appropriate engineering						
controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed					

engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection	
Eye and face protection	No special equipment for minor exposure i.e. when handling small quantities. OTHERWISE: For potentially moderate or heavy exposures: • Safety glasses with side shields. • NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.
Skin protection	See Hand protection below
Hands/feet protection	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. • Neoprene rubber gloves • No special equipment needed when handling small quantities. • OTHERWISE: • For potentially moderate exposures: • Wear general protective gloves, eg. light weight rubber gloves. • For potentially heavy exposures: • Wear chemical protective gloves, eg. PVC. and safety footwear.
Body protection	See Other protection below
Other protection	 The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton. Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost. BRETHERICK: Handbook of Reactive Chemical Hazards. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. No special equipment needed when handling small quantities. OTHERWISE: Overalls. Skin cleansing cream. Eyewash unit.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

CRC (NZ) 5087 Brakleen Blaster Aerosol

Material	CPI
BUTYL	С
CPE	С
HYPALON	С
NATURAL RUBBER	С
NEOPRENE	С
NITRILE	С
NITRILE+PVC	С
PE/EVAL/PE	С
PVA	С
PVC	C
SARANEX-23	С
SARANEX-23 2-PLY	С
TEFLON	С

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS	-	AX-PAPR-AUS / Class 1
up to 50 x ES	-	AX-AUS / Class 1	-
up to 100 x ES	-	AX-2	AX-PAPR-2 ^

^ - Full-face

 $\begin{array}{l} \mbox{A(All classes)} = \mbox{Organic vapours, B AUS or B1} = \mbox{Acid gasses, B2} = \mbox{Acid gas} \\ \mbox{or hydrogen cyanide(HCN), B3} = \mbox{Acid gas or hydrogen cyanide(HCN), E} = \\ \mbox{Sulfur dioxide(SO2), G} = \mbox{Agricultural chemicals, K} = \mbox{Ammonia(NH3), Hg} = \\ \mbox{Mercury, NO} = \mbox{Oxides of nitrogen, MB} = \mbox{Methyl bromide, AX} = \mbox{Low boiling} \\ \mbox{point organic compounds(below 65 degC)} \end{array}$

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately

	1
VITON	С
VITON/BUTYL	С
VITON/CHLOROBUTYL	С
VITON/NITRILE	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

 $\ensuremath{\text{NOTE}}$: As a series of factors will influence the actual performance of the glove,

a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance Clear, water white, flammable liquid with an ethereal odour; not miscible with water. Supplied as an aerosol pack. Contents under PRESSURE. Contains carbon dioxide propellant.

	·		
Physical state	Liquid	Relative density (Water = 1)	1.07
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	40 initial	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	10	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	22	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.4	Volatile Component (%vol)	100
Vapour pressure (kPa)	26.6 @ 20 C	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Applicable
Vapour density (Air = 1)	>1	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7		
Chemical stability	 Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur. 		
Possibility of hazardous reactions	See section 7		
Conditions to avoid	See section 7		
Incompatible materials	See section 7		
Hazardous decomposition products	See section 5		

SECTION 11 Toxicological information

Information on toxicological effects

	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of
Inhaled	reflexes, lack of co-ordination, and vertigo.

on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used
- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

	health of the individual.	naterial during the course of normal handling, may be damaging to the a cause respiratory irritation in some persons. The body's response to	
	such irritation can cause further lung damage.		
		ung irritation with coughing and nausea, central nervous depression with	
		general discomfort, symptoms of giddiness, headache, dizziness,	
	may result in respiratory depression and may be fatal.	ed speech and may progress to unconsciousness. Serious poisonings neptanes for 6 minutes was associated with slight dizziness; inhalation of	
	involvement occurs very early, even before mucous mer	tigo and inco-ordination, and hilarity. Central nervous system nbrane irritation. Animal testing showed exposure to 1.5-2% for 30 6 caused nausea, loss of appetite, and a "gasoline taste" that persisted	
		s appears to take place over two stages. Signs of a reversible narcosis ns of injury to organs may become evident, a single organ alone is	
	and excitation, passing into narcosis, is a typical reactio	utstanding effect of most halogenated aliphatic hydrocarbons. Inebriation n. In severe acute exposures there is always a danger of death from make the heart more susceptible to catecholamines (adrenalin)	
		trated atmosphere in confined or unventilated areas. The vapour may imple asphyxiant. This may happen with little warning of overexposure.	
	Exposure to high levels of tetrachloroethylene by oral or behavioural changes, seizure, unconsciousness, abnorr	inhalation may cause dose dependent light-headedness, mood and nal bilirubin level, liver and kidney damage in workers. Sudden death ession of the respiratory centre or heart dysfunction. Human studies	
Ingestion	Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) Accidental ingestion of the material may be damaging to the health of the individual. When tetrachloroethylene is used in the treatment of hookworm (4.5 to 6.5 gm orally) the only adverse effect is a drunken-like		
	state. Transient liver toxicity in patients given single oral	· · · · · · · · · · · · · · · · · · ·	
	Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. There is some evidence to suggest that the material may cause significant and severe inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. Spray mist may produce discomfort Fluorocarbons remove natural oils from the skin, causing irritation, dryness and sensitivity.		
Skin Contact	Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Industrial experience shows that exposure to tetrachloroethylene produces localised skin irritation while prolonged skin contact can cause chemical burns and blistering. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation.		
	Limited evidence or practical experience suggests, that	the material may cause eye irritation in a substantial number of the same as for inhalation.	
Eye	windburn). Not considered to be a risk because of the extreme vola Irritation of the eyes may produce a heavy secretion of t	tility of the gas.	
	Exposure to high concentrations of tetrachloroethylene vapour causes mild to severe eye irritation, burning or stinging sensations depending on the dose and duration of exposure. Colour vision has equally being reported which is attributed to neurological rather than a direct effect on the eyes.		
	There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.		
	occupational exposure.	and may cause some concern following repeated or long-term	
Chronic	occupational exposure. There is some evidence from animal testing that exposu There is some evidence from animal testing that exposu Main route of exposure to the gas in the workplace is by Exposure to tetrachloroethylene noted in dry cleaners c	and may cause some concern following repeated or long-term re to this material may result in reduced fertility. re to this material may result in toxic effects to the unborn baby. inhalation. auses menstrual disorder and miscarriage, liver dysfunction, headache	
Chronic	occupational exposure. There is some evidence from animal testing that exposu There is some evidence from animal testing that exposu Main route of exposure to the gas in the workplace is by Exposure to tetrachloroethylene noted in dry cleaners of and dizziness. Studies done showed high mortality rate lymph/blood system, and colon in dry cleaners and laun laundry and dry cleaners. However, there is not sufficier The reactivity of an epoxide intermediate may be the rear reported that 1,1-dichloroethyne, vinyl chloride, trichloro	and may cause some concern following repeated or long-term re to this material may result in reduced fertility. re to this material may result in toxic effects to the unborn baby. inhalation. auses menstrual disorder and miscarriage, liver dysfunction, headache resulting from cancers of the lung, cervix, gullet, kidney, skin, dry workers. Liver cancer was detected in females but none in male	
Chronic	occupational exposure. There is some evidence from animal testing that exposu There is some evidence from animal testing that exposu Main route of exposure to the gas in the workplace is by Exposure to tetrachloroethylene noted in dry cleaners of and dizziness. Studies done showed high mortality rate lymph/blood system, and colon in dry cleaners and laun laundry and dry cleaners. However, there is not sufficier The reactivity of an epoxide intermediate may be the rear reported that 1,1-dichloroethyne, vinyl chloride, trichloro Generally speaking, substances with one halogen subst	and may cause some concern following repeated or long-term inter to this material may result in reduced fertility. Inter to this material may result in toxic effects to the unborn baby. Inhalation. auses menstrual disorder and miscarriage, liver dysfunction, headache resulting from cancers of the lung, cervix, gullet, kidney, skin, dry workers. Liver cancer was detected in females but none in male at statistical data to make an absolute conclusion. ason for the cancer-causing properties of halogenated oxiranes. It is ethylene, tetrachloroethylene and chloroprene all cause cancer.	
	occupational exposure. There is some evidence from animal testing that exposu There is some evidence from animal testing that exposu Main route of exposure to the gas in the workplace is by Exposure to tetrachloroethylene noted in dry cleaners of and dizziness. Studies done showed high mortality rate lymph/blood system, and colon in dry cleaners and laun laundry and dry cleaners. However, there is not sufficier The reactivity of an epoxide intermediate may be the rear reported that 1,1-dichloroethyne, vinyl chloride, trichloro Generally speaking, substances with one halogen subst	and may cause some concern following repeated or long-term are to this material may result in reduced fertility. The to this material may result in toxic effects to the unborn baby. The inhalation. The auses menstrual disorder and miscarriage, liver dysfunction, headache resulting from cancers of the lung, cervix, gullet, kidney, skin, dry workers. Liver cancer was detected in females but none in male th statistical data to make an absolute conclusion. The cancer-causing properties of halogenated oxiranes. It is ethylene, tetrachloroethylene and chloroprene all cause cancer.	
Chronic CRC (NZ) 5087 Brakleen Blaster Aerosol	occupational exposure. There is some evidence from animal testing that exposu There is some evidence from animal testing that exposu Main route of exposure to the gas in the workplace is by Exposure to tetrachloroethylene noted in dry cleaners ci and dizziness. Studies done showed high mortality rate lymph/blood system, and colon in dry cleaners and laun laundry and dry cleaners. However, there is not sufficier The reactivity of an epoxide intermediate may be the rear reported that 1,1-dichloroethyne, vinyl chloride, trichloro Generally speaking, substances with one halogen subst with two.	and may cause some concern following repeated or long-term are to this material may result in reduced fertility. The to this material may result in toxic effects to the unborn baby. Inhalation. auses menstrual disorder and miscarriage, liver dysfunction, headache resulting from cancers of the lung, cervix, gullet, kidney, skin, dry workers. Liver cancer was detected in females but none in male at statistical data to make an absolute conclusion. ason for the cancer-causing properties of halogenated oxiranes. It is ethylene, tetrachloroethylene and chloroprene all cause cancer. itution show higher potential to cause cancer compared to substances	
CRC (NZ) 5087 Brakleen	occupational exposure. There is some evidence from animal testing that exposu There is some evidence from animal testing that exposu Main route of exposure to the gas in the workplace is by Exposure to tetrachloroethylene noted in dry cleaners of and dizziness. Studies done showed high mortality rate lymph/blood system, and colon in dry cleaners and laun laundry and dry cleaners. However, there is not sufficien The reactivity of an epoxide intermediate may be the rear reported that 1,1-dichloroethyne, vinyl chloride, trichloro Generally speaking, substances with one halogen subst with two.	and may cause some concern following repeated or long-term are to this material may result in reduced fertility. are to this material may result in toxic effects to the unborn baby. inhalation. auses menstrual disorder and miscarriage, liver dysfunction, headache resulting from cancers of the lung, cervix, gullet, kidney, skin, dry workers. Liver cancer was detected in females but none in male at statistical data to make an absolute conclusion. ason for the cancer-causing properties of halogenated oxiranes. It is ethylene, tetrachloroethylene and chloroprene all cause cancer. itution show higher potential to cause cancer compared to substances IRRITATION	
CRC (NZ) 5087 Brakleen	occupational exposure. There is some evidence from animal testing that exposu There is some evidence from animal testing that exposu Main route of exposure to the gas in the workplace is by Exposure to tetrachloroethylene noted in dry cleaners ca and dizziness. Studies done showed high mortality rate lymph/blood system, and colon in dry cleaners and laun laundry and dry cleaners. However, there is not sufficient The reactivity of an epoxide intermediate may be the react reported that 1,1-dichloroethyne, vinyl chloride, trichloro Generally speaking, substances with one halogen substances with two. TOXICITY Not Available	and may cause some concern following repeated or long-term are to this material may result in reduced fertility. Ire to this material may result in toxic effects to the unborn baby. inhalation. auses menstrual disorder and miscarriage, liver dysfunction, headache resulting from cancers of the lung, cervix, gullet, kidney, skin, dry workers. Liver cancer was detected in females but none in male it statistical data to make an absolute conclusion. ason for the cancer-causing properties of halogenated oxiranes. It is ethylene, tetrachloroethylene and chloroprene all cause cancer. itution show higher potential to cause cancer compared to substances IRRITATION Not Available	

	Oral (Rat) LD50; 2629 mg/kg ^[2]	Skin (rabbit): 810 mg/24h -SEVERE
		Skin: adverse effect observed (irritating) ^[1]
		Skin: no adverse effect observed (not irritating) ^[1]
	ΤΟΧΙΟΙΤΥ	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[2]	Eye(rabbit): 162 mg - moderate
methylene chloride	Inhalation(Rat) LC50; 76 mg/L4h ^[2]	Eye(rabbit): 500 mg/24hr - mild
	Oral (Rat) LD50; 1600 mg/kg ^[2]	Skin (rabbit): 100mg/24hr-moderate
		Skin (rabbit): 810 mg/24hr-SEVERE
	ΤΟΧΙΟΙΤΥ	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
heptane	Inhalation(Rat) LC50; >29.29 mg/l4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50; >5000 mg/kg ^[1]	
	ΤΟΧΙΟΙΤΥ	IRRITATION
carbon dioxide	Not Available	Not Available
Legend:	 Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances 	

PERCHLOROETHYLENE	Disinfection byproducts (DBPs) are formed when disinfectants such as chlorine, chloramines and ozone react with organic and inorganic matter in water. Animal studies have shown that some DBPs cause cancer. To date, several hundred DBPs have bee identified. Numerous haloalkanes and haloalkenes have been tested for cancer-causing and mutation-causing activities. In general, the potential to cause genetic toxicity is dependent on the nature, number and position of halogen(s) and the size of the molecule.		
METHYLENE CHLORIDE	Inhalation (human) TCLo: 500 ppm/ 1 y - I Eye(rabbit): 10 mg - mild The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.		
CRC (NZ) 5087 Brakleen Blaster Aerosol & PERCHLOROETHYLENE	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.		
CRC (NZ) 5087 Brakleen	The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.		
Blaster Aerosol & PERCHLOROETHYLENE & METHYLENE CHLORIDE	-		
PERCHLOROETHYLENE &	-	thickening of the skin. Repeated	exposures may produce severe ulceration.
PERCHLOROETHYLENE & METHYLENE CHLORIDE PERCHLOROETHYLENE &	swelling, the production of vesicles, scaling and	thickening of the skin. Repeated	exposures may produce severe ulceration.
PERCHLOROETHYLENE & METHYLENE CHLORIDE PERCHLOROETHYLENE & METHYLENE CHLORIDE	swelling, the production of vesicles, scaling and WARNING: This substance has been classified	thickening of the skin. Repeated by the IARC as Group 2A: Proba	exposures may produce severe ulceration. bly Carcinogenic to Humans.
PERCHLOROETHYLENE & METHYLENE CHLORIDE PERCHLOROETHYLENE & METHYLENE CHLORIDE Acute Toxicity	swelling, the production of vesicles, scaling and WARNING: This substance has been classified	thickening of the skin. Repeated by the IARC as Group 2A: Proba	exposures may produce severe ulceration. bly Carcinogenic to Humans.
PERCHLOROETHYLENE & METHYLENE CHLORIDE PERCHLOROETHYLENE & METHYLENE CHLORIDE Acute Toxicity Skin Irritation/Corrosion Serious Eye	warning: This substance has been classified	thickening of the skin. Repeated by the IARC as Group 2A: Proba Carcinogenicity Reproductivity	exposures may produce severe ulceration. bly Carcinogenic to Humans.

Data available to make classification

SECTION 12 Ecological information

CRC (NZ) 5087 Brakleen Blaster Aerosol	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
perchloroethylene	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	3.1-4.18mg/l	4
	EC50	48h	Crustacea	22mg/l	1
	EC50	96h	Algae or other aquatic plants	500mg/l	1
	EC50(ECx)	24h	Crustacea	3.2mg/l	1

	BCF	1344h	Fish	25.8-77.1	7
	LC50	96h	Fish	>3<6mg/l	4
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	96h	Algae or other aquatic plants	0.98mg/l	4
	BCF	1008h	Fish	2-5.4	7
methylene chloride	LC50	96h	Fish	2-3.3mg/l	4
	EC50	72h	Algae or other aquatic plants	202-286mg/l	4
	EC50	48h	Crustacea	150-218mg/l	4
	EC50	96h	Algae or other aquatic plants	0.98mg/l	4
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	504h	Crustacea	0.17mg/l	2
heptane	LC50	96h	Fish	3446.8mg/L	4
	EC50	48h	Crustacea	0.64mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
carbon dioxide	LC50	96h	Fish	35mg/l	1
Legend:	4. US EPA, Ec		IA Registered Substances - Ecotoxicologi ECETOC Aquatic Hazard Assessment D	•	tic Toxicit

Substances containing unsaturated carbons are ubiquitous in indoor environments. They result from many sources (see below). Most are reactive with environmental ozone and many produce stable products which are thought to adversely affect human health. The potential for surfaces in an enclosed space to facilitate reactions should be considered.

Source of unsaturated substances Unsaturated substances (Reactive Emissions) Major Stable Products produced following reaction with ozone. For Haloalkanes:

Atmospheric Fate: Fully, or partially, fluorinated haloalkanes released to the air can restrict heat loss from the Earth's atmosphere by absorbing infrared emissions from the surface. The major fate of haloalkanes in the atmosphere is via breakdown by hydroxyl radicals. These substances react with atmospheric ozone and nitrates, which also causes them to change, (transform). Chlorofluorocarbons, (CFC), haloalkanes can break down into chlorine atoms in the air, which also contribute to ozone destruction.

For n-Heptane: Log Kow: 4.66; Koc: 2400-8100; Half-life (hr) Air: 52.8; Half-life (hr) Surface Water: 2.9-312; Henry's atm m3 /mol: 2.06; BOD 5 (if unstated): 1.92; COD: 0.06; BCF: 340-2000; Log BCF: 2.53-3.31.

Atmospheric Fate: Breakdown of n-heptane by sunlight is not expected to be an important fate process. If released to the atmosphere, n-heptane is expected to exist entirely in the vapor phase, in ambient air. Reactions hydroxyl radicals in the atmosphere have been shown to be important.

For Tetrachloroethylene (Synonym: Perchloroethylene): log Koc: 2.38 - 2.9. 7; Koc: 209 – 1685; Half-life (hr) H2O surface water: 26.4-2664; Henry's atm m3 /mol: 1.49E-02; BOD 5: 0.06; COD: 0.39; BCF: 38.9-226; Log BCF: 1.59.

Atmospheric Fate: Long-range global transport of tetrachloroethylene is likely. Dry deposition does not appear to be a significant removal process, although substantial evaporation from dry surfaces can be predicted.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
perchloroethylene	HIGH (Half-life = 720 days)	MEDIUM (Half-life = 160.13 days)
methylene chloride	LOW (Half-life = 56 days)	HIGH (Half-life = 191 days)
heptane	LOW	LOW
carbon dioxide	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
perchloroethylene	LOW (BCF = 77.1)
methylene chloride	LOW (BCF = 40)
heptane	HIGH (LogKOW = 4.66)
carbon dioxide	LOW (LogKOW = 0.83)

Mobility in soil

Ingredient	Mobility
perchloroethylene	LOW (KOC = 106.8)
methylene chloride	LOW (KOC = 23.74)
heptane	LOW (KOC = 274.7)
carbon dioxide	HIGH (KOC = 1.498)

SECTION 13 Disposal considerations

Waste treatment methods

 Product / Packaging disposal It may be necessary to collect all wash water for treatment before disposal. It may be necessary to collect all wash water for treatment before disposal. It may be necessary to collect all wash water for treatment before disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to collect all wash water for disposal. It may be necessary to disposal disposal to sever may be subject to local laws and regulations and these should be considered first. It may be may be authority. It may be may be authority. It may be may be authority for disposal. It may be may be authority for di		
disposal DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. 		operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: • Reduction • Reuse • Recycling
 It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. 	Product / Packaging	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.
 In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. 	disposal	DO NOT allow wash water from cleaning or process equipment to enter drains.
 Where in doubt contact the responsible authority. Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. 		It may be necessary to collect all wash water for treatment before disposal.
 Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. 		In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
 Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. 		Where in doubt contact the responsible authority.
Allow small quantities to evaporate.		Consult State Land Waste Management Authority for disposal.
		Discharge contents of damaged aerosol cans at an approved site.
DO NOT incinerate or puncture aerosol cans.		Allow small quantities to evaporate.
		DO NOT incinerate or puncture aerosol cans.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017


Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 Transport information

Labels Required



Land transport (UN)

UN number	1950	1950	
UN proper shipping name	AEROSOLS	AEROSOLS	
Transport hazard class(es)	Class 2.1 Subrisk Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Environmentally hazardous		
Special precautions for user	Special provisions 63; 190; 277; 327; 344; 381 Limited quantity 1000ml		

Air transport (ICAO-IATA / DGR)

UN number	1950			
UN proper shipping name	Aerosols, flammable			
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	2.1 Not Applicable 10L		
Packing group	Not Applicable			

Environmentally hazardous		
Special provisions A145 A167 A802		
Cargo Only Packing Instructions	203	
Cargo Only Maximum Qty / Pack	150 kg	
Passenger and Cargo Packing Instructions	203	
Passenger and Cargo Maximum Qty / Pack	75 kg	
Passenger and Cargo Limited Quantity Packing Instructions	Y203	
Passenger and Cargo Limited Maximum Qty / Pack	30 kg G	
	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instructions	

Sea transport (IMDG-Code / GGVSee)

UN number	1950		
UN proper shipping name	AEROSOLS		
Transport hazard class(es)	IMDG Class2.1IMDG SubriskNot Applicable		
Packing group	Not Applicable		
Environmental hazard	Marine Pollutant		
Special precautions for user	EMS Number Special provisions Limited Quantities	F-D , S-U 63 190 277 327 344 381 959 1000 ml	

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
perchloroethylene	Not Available
methylene chloride	Not Available
heptane	Not Available
carbon dioxide	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
perchloroethylene	Not Available
methylene chloride	Not Available
heptane	Not Available
carbon dioxide	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard	
HSR002517	Aerosols Flammable Toxic(6.7) Group Standard 2017	

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

perchloroethylene is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2A: Probably carcinogenic to humans

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act -Classification of Chemicals New Zealand Hazardous Substances and New Organisms (HSNO) Act -Classification of Chemicals - Classification Data New Zealand Inventory of Chemicals (NZIoC) New Zealand Workplace Exposure Standards (WES)

methylene chloride is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List	New Zealand Hazardous Substances and New Organisms (HSNO) Act -	
International Agency for Research on Cancer (IARC) - Agents Classified by	Classification of Chemicals	
the IARC Monographs	New Zealand Hazardous Substances and New Organisms (HSNO) Act -	
International Agency for Research on Cancer (IARC) - Agents Classified by	Classification of Chemicals - Classification Data	
the IARC Monographs - Group 2A: Probably carcinogenic to humans	New Zealand Inventory of Chemicals (NZIoC)	
New Zealand Approved Hazardous Substances with controls	New Zealand Workplace Exposure Standards (WES)	
bostone is found on the following regulatory lists		
heptane is found on the following regulatory lists		
New Zealand Approved Hazardous Substances with controls	New Zealand Inventory of Chemicals (NZIoC)	
New Zealand Hazardous Substances and New Organisms (HSNO) Act -	New Zealand Workplace Exposure Standards (WES)	
Classification of Chemicals		
New Zealand Hazardous Substances and New Organisms (HSNO) Act -		
Classification of Chemicals - Classification Data		
1		
carbon dioxide is found on the following regulatory lists		
FEI Equine Prohibited Substances List - Controlled Medication	New Zealand Hazardous Substances and New Organisms (HSNO) Act -	
FEI Equine Prohibited Substances List (EPSL)	Classification of Chemicals - Classification Data	
New Zealand Approved Hazardous Substances with controls	New Zealand Inventory of Chemicals (NZIoC)	
New Zealand Hazardous Substances and New Organisms (HSNO) Act -	New Zealand Workplace Exposure Standards (WES)	
Classification of Chemicals		

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
2.1.2A	3 000 L (aggregate water capacity)	3 000 L (aggregate water capacity)

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
2.1.2A				1L (aggregate water capacity)

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (perchloroethylene; methylene chloride; heptane; carbon dioxide)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes

National Inventory	Status	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	10/12/2021
Initial Date	06/07/2009

SDS Version Summary

Version	Date of Update	Sections Updated
5.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
6.1	10/12/2021	Classification change due to full database hazard calculation/update.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC	C-TWA: Permissible Concentration-Time Weighted Average
	C-STEL: Permissible Concentration-Short Term Exposure Limit
IA	RC: International Agency for Research on Cancer
AC	CGIH: American Conference of Governmental Industrial Hygienists
ST	EL: Short Term Exposure Limit
TE	EL: Temporary Emergency Exposure Limit。
ID	LH: Immediately Dangerous to Life or Health Concentrations
ES	S: Exposure Standard
08	SF: Odour Safety Factor
N	DAEL :No Observed Adverse Effect Level
LC	DAEL: Lowest Observed Adverse Effect Level
TL	V: Threshold Limit Value
LC	DD: Limit Of Detection
O	TV: Odour Threshold Value
BC	CF: BioConcentration Factors
BE	El: Biological Exposure Index
AI	IC: Australian Inventory of Industrial Chemicals
DS	SL: Domestic Substances List
NE	DSL: Non-Domestic Substances List
IE	CSC: Inventory of Existing Chemical Substance in China
EI	NECS: European INventory of Existing Commercial chemical Substances
EL	INCS: European List of Notified Chemical Substances
NL	P: No-Longer Polymers
E١	VCS: Existing and New Chemical Substances Inventory
KE	ECI: Korea Existing Chemicals Inventory
NZ	ZIOC: New Zealand Inventory of Chemicals
Pl	CCS: Philippine Inventory of Chemicals and Chemical Substances
TS	SCA: Toxic Substances Control Act
тс	CSI: Taiwan Chemical Substance Inventory
IN	SQ: Inventario Nacional de Sustancias Químicas
NC	CI: National Chemical Inventory
FE	3EPH: Russian Register of Potentially Hazardous Chemical and Biological Substances
Th	is document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.