

## RED RUBBER GREASE

**RED RUBBER GREASE** is a premium quality clay thickened grease formulated with castor oil. **RED RUBBER GREASE** provides outstanding performance in a wide range of applications where contact with rubber compounds is likely or required.

**RED RUBBER GREASE** is recommended as a general purpose, rubber compatible grease for automotive and industrial components consisting of natural or synthetic rubber.

### *Benefits*

- Compatible with natural and synthetic rubber compounds
- Excellent lubricity
- Protects against rust and corrosion
- Environmentally friendly formulation

### *Physical/Chemical Properties*

TEST	ASTM METHOD	TYPICAL RESULT
NLGI Grade		2
Thickener Type		Clay
Colour/Appearance		Red/Tacky
Worked Penetration (60 strokes)	D.217	280
Drop Point (°C)	D.2265	288+
Base Oil Viscosity (cSt)	D.445	250

Imported and distributed by

**Oil Intel Ltd**

56 Whakatu Road, Whakatu, Hastings 4172.

PO Box 13 049, Mahora, Hastings 4155.

Phone: 06 871 5325 Fax: 06 870 4890.

Email: [office@oilimports.co.nz](mailto:office@oilimports.co.nz)

[www.oilintel.co.nz](http://www.oilintel.co.nz)