SAFETY DATA SHEET



MOBIL DELVAC MODERN 15W-40 FULL PROTECTION

Section 1. Identification

Product name	: MOBIL DELVAC MODERN 15W-40 FULL PROTECTION
Product description	: base oil and additives
Relevant identified uses of	the substance or mixture and uses advised against
Identified uses	: Engine oil
Uses advised against	: This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above.
Supplier	: AMPOL AUSTRALIA PETROLEUM PTY LTD ABN 17 000 032 128 29-33 Bourke Rd Alexandria New South Wales 2015 Australia
24 Hour Emergency Telephone	: +61 2 9037 2994/1800 862 115 (CHEMTREC)
Product Technical Information	: 1300364169
Supplier General Contact	: +612 9250-5000
FAX	: +612 9250-5742
SDS Internet Address	: www.sds.exxonmobil.com

Section 2. Hazard(s) identification

Classification of the substance or mixture	: Not classifie	:d.
Other hazards which do not result in classification	: None knowr	۱.
Nota	: This materia Section 1 w	ithout ex

: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

Section 3. Composition and ingredient information

Substance/mixture

: Mixture

Ingredient name	% (w/w)	Identifiers
distillates (petroleum), solvent-dewaxed light paraffinic	≤3	CAS: 64742-56-9
distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	CAS: 64742-65-0
paraffin oils (petroleum), catalytic dewaxed heavy	≤3	CAS: 64742-70-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures		
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs. 	
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.	
Skin contact	: Mush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.	
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.	

Most important symptoms/effects, acute and delayed

Potential acute health e	ffects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sy	r <u>mptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Cocal necrosis as evidenced by delayed onset of pain and tissue damage a few hours after injection.
Ingestion	: No specific data.
Indication of immediate I	nedical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large

Notes to physician	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Adehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, sulfur oxides

Section 5. Firefighting measures

Special protective actions for fire-fighters	:	Use standard firefighting procedures and consider the hazards of other involved materials. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Assure an extended cooling down period to prevent re- ignition. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	-	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	; ;	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and material for co	nta	inment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Confine the spill immediately

with booms. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants. Warn other shipping. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Avoid contact with used product.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Static Accumulator	: This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semiconductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semiconductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives and filtration can greatly influence the conductivity of a liquid.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
stillates (petroleum), hydrotreated heavy	Safe Work Australia (Australia, 1/2024) [Oil mist, refined
paraffinic	mineral]
	TWA 8 hours: 5 mg/m ³ . Form: Mist.
	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly and severely refined]
	TWA 8 hours: 5 mg/m ³ . Form: Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic	Safe Work Australia (Australia, 1/2024) [Oil mist, refined mineral]
	TWA 8 hours: 5 mg/m ³ . Form: Mist.
	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly
	and severely refined]
	TWA 8 hours: 5 mg/m ³ . Form: Inhalable fraction.
distillates (petroleum), solvent-dewaxed light	Safe Work Australia (Australia, 1/2024) [Oil mist, refined
paraffinic	mineral]
	TWA 8 hours: 5 mg/m ³ . Form: Mist.
	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly
	and severely refined]
	TWA 8 hours: 5 mg/m ³ . Form: Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy	Safe Work Australia (Australia, 1/2024) [Oil mist, refined
paraffinic	mineral]
	TWA 8 hours: 5 mg/m ³ . Form: Mist.
	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly
	and severely refined]
.	TWA 8 hours: 5 mg/m ³ . Form: Inhalable fraction.
paraffin oils (petroleum), catalytic dewaxed	Safe Work Australia (Australia, 1/2024) [Oil mist, refined
heavy	mineral]
	TWA 8 hours: 5 mg/m ³ . Form: Mist.
	ACGIH TLV (United States, 1/2024) [Mineral Oil, pure, highly
	and severely refined]
	TWA 8 hours: 5 mg/m ³ . Form: Inhalable fraction.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

Appropriate engineering	:	Good general ventilation should be sufficient to control worker exposure to airborne
controls		contaminants.

Date of issue/Date of revision

Section 8. Exposure controls and personal protection

: Emissions from ventilation or work process equipment should be checked to ensur they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	
nds, forearms and face thoroughly after handling chemical products, before moking and using the lavatory and at the end of the working period. ate techniques should be used to remove potentially contaminated clothing. ntaminated clothing before reusing. Ensure that eyewash stations and owers are close to the workstation location.	
vewear complying with an approved standard should be used when a risk ent indicates this is necessary to avoid exposure to liquid splashes, mists, dusts. If contact is possible, the following protection should be worn, e assessment indicates a higher degree of protection: safety glasses with lds.	
l-resistant, impervious gloves complying with an approved standard should at all times when handling chemical products if a risk assessment indicates cessary.	
protective equipment for the body should be selected based on the task formed and the risks involved and should be approved by a specialist andling this product.	
ate footwear and any additional skin protection measures should be based on the task being performed and the risks involved and should be I by a specialist before handling this product.	
n the hazard and potential for exposure, select a respirator that meets the ate standard or certification. Respirators must be used according to a ry protection program to ensure proper fitting, training, and other important of use.	

Section 9. Physical and chemical properties and safety characteristics

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Liquid.
Colour	: Amber
Odour	: 🗭haracteristic
Odour threshold	: Not available.
рН	: Not applicable.
Melting point/freezing point	: Not available.
Boiling point or initial boiling point and boiling range	: ▶315.56°C (>600°F)
Flash point	: Øpen cup: >215°C (>419°F) [ASTM D-92]
Evaporation rate	: Not available.
Flammability	: Ignitable
Lower and upper explosion limit/flammability limit	: Kower: 0.9% Upper: 7%
Vapour pressure	: 📈.1 mm Hg [20 °C]
	: Not available.

Date of issue/Date of revision

Section 9. Physical and chemical properties and safety characteristics

Relative density	1	Ø .875
Solubility in water	:	Negligible
Partition coefficient: n- octanol/water	:	▶3.5
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	14 cSt [40 °C] [ASTM D 445] 14 cSt [100 °C] [ASTM D 445]
Particle characteristics		
Median particle size	1	Not applicable.
Particle characteristics		
Median particle size	:	Not applicable.
Pour point	:	- ∕27°C
DMSO Extract (mineral oil only), IP-346	:	✓3 % by weight

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: High energy sources of ignition. Excessive heat.
Incompatible materials	: Strong oxidisers
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity	
Conclusion/Summary	
Inhalation	 Minimally Toxic. No end point data for material. Based on assessment of the components.
Dermal	 Minimally Toxic. No end point data for material. Based on assessment of the components.
Oral	: Minimally Toxic. No end point data for material. Based on assessment of the components.
Irritation/Corrosion	
Conclusion/Summary	
Skin	: Megligible irritation to skin at ambient temperatures. No end point data for material. Based on assessment of the components.
Eyes	: May cause mild, short-lasting discomfort to eyes. No end point data for material. Based on assessment of the components.
Respiratory	: Megligible hazard at ambient/normal handling temperatures. No end point data for material.
Poopiratory or akin appai	tization

Respiratory or skin sensitization

Date of issue/Date of revision	: 1 May 2025	Date of previous issue	: 28 August 2024	Version : 1.03	6/10
--------------------------------	--------------	------------------------	------------------	----------------	------

Section 11. Toxicological information

Conclusion/Summary			
Skin		: Not expected to be a skin sensitizer. No end point data for material. Based on assessment of the components.	
Respiratory	: Not expected to be a res	piratory sensitizer. No ene	d point data for material.
Mutagenicity			
Conclusion/Summary	: Not expected to be a gen assessment of the compo		point data for material. Based on
Carcinogenicity			
Conclusion/Summary	: Not expected to cause ca of the components.	ancer. No end point data i	for material. Based on assessment
Reproductive toxicity			
Conclusion/Summary	: Not expected to be a repr assessment of the compo	roductive toxicant. No enconents.	d point data for material. Based on
Specific target organ toxi	<u>icity (single exposure)</u>		
Conclusion/Summary	: Not expected to cause or material.	gan damage from a single	e exposure. No end point data for
Specific target organ toxi	icity (repeated exposure)		
Product/ingredient name	•	Category	Target organs
MOBIL DELVAC MODERN	N 15W-40 FULL PROTECTION	Not applicable.	-
Conclusion/Summary		gan damage from prolong ased on assessment of th	ged or repeated exposure. No end e components.
Aspiration hazard			
Conclusion/Summary	: Not expected to be an as the material. Data availa		n physico-chemical properties of
Other information			
Contains	passes IP-346, Modified inhalation studies showed	Ames test, and/or other so d minimal effects; lung no	nal studies. Representative material creening tests. Dermal and n-specific infiltration of immune on. Not sensitising in test animals.
Product	oils did not produce any o Oils that are used in gaso following properties: Car allergen and photoallerge	carcinogenic effects in chr oline engines may become cinogenic in animal tests.	ts. Used and unused diesel engine onic mouse skin painting studies. hazardous and display the Caused mutations in vitro. Possible matic compounds (PAC) from gradation products.

Section 12. Ecological information

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

 Toxicity
 Conclusion/Summary

 Acute toxicity
 : Not expected to be harmful to aquatic organisms.

 Chronic toxicity
 : Not expected to demonstrate chronic toxicity to aquatic organisms

 Persistence and degradability
 : Mot expected to demonstrate chronic toxicity to aquatic organisms

 Biodegradability
 : Sase oil component -- Expected to be inherently biodegradable

 Bioaccumulative potential Conclusion/Summary
 : Sase oil component -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

Section 12. Ecological information

Mobility in soil

Mobility

: Base oil component -- Expected to partition to sediment and wastewater solids. Low solubility and floats and is expected to migrate from water to the land.

Other ecological information

Section 13. Disposal considerations

Disposal methods 2 The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

> Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably gualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Section 14. Transport information

	ADG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments

: Not applicable.

Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

Inventory list	
Australia inventory (AIIC)	: Restrictions Apply
Canada inventory (DSL-NDSL)	: 🕅 components are listed or exempted.
China inventory (IECSC)	: Restrictions Apply
Japan inventory (CSCL)	: 🕅 components are listed or exempted.
Japan inventory (Industrial Safety and Health Act)	: 🕅 components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC)	: 🕅 components are listed or exempted.
Philippines inventory (PICCS)	: 🕅 components are listed or exempted.
Korea inventory (KECI)	: Restrictions Apply
Taiwan Chemical Substances Inventory (TCSI)	: Restrictions Apply
United States inventory (TSCA 8b)	: All components are active or exempted.

Section 16. Any other relevant information

History	
Date of issue/Date of revision	: 1 May 2025
Date of previous issue	: 28 August 2024
Version	: 1.03
Key to abbreviations	 ADG = Australian Dangerous Goods ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group SUSMP = Standard Uniform Schedule of Medicine and Poisons UN = United Nations
Drocodure used to derive th	a classification

Procedure used to derive the classification

Not classified.

References : Not available.

Indicates information that has changed from previously issued version.

Product code : 20152040U710_1166485

Notice to reader

"The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this

Date of issue/Date of revision

Section 16. Any other relevant information

document, in whole or in part, is not permitted. The term, ""ExxonMobil"" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest."