



MOTUL GARDEN 4T SAE 30

4 Stroke Engine Lubricant for Motorised Garden Tools

Gasoline Engine

SAE 30

TYPE OF USE

**Specially Formulated for Motorised Garden Tools and Small Farming Machines
All Gasoline 4 Stroke Engines**

Lawn mowers, motor mowers, light tractors...

Suitable for all types of fuel: leaded and unleaded gasoline, diesel fuel.

All types of 4 stroke engines with or without catalytic converter.

PERFORMANCE

STANDARDS: API SG / CD

Ensures the engine cleanliness

Protection during wintering

Dispersant and detergent properties

Good cold starting, perfectly stable in a hot engine

Anti-oxidation, Anti-wear properties.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.
MOTUL GARDEN 4T SAE 30 can be mixed with synthetic or mineral lubricants.

PROPERTIES

Mineral multigrade lubricant.

Viscosity grade

Density at 15°C (59°F)

Viscosity at 40°C (104°F)

Viscosity at 100°C (212°F)

Viscosity index (VIE)

Flash point

Pour point

TBN

SAE J 300	30
ASTM D 1298	0.882
ASTM D 445	83.4 mm ² /s
ASTM D 445	10.7 mm ² /s
ASTM D 2270	113
ASTM D 92	224°C / 435°F
ASTM D 97	-24°C / -11°F
ASTM D 2896	6.7 mg KOH/g