



MOTUL GARDEN 2T Hi-Tech

2 Stroke Engine Lubricant for Motorised Garden Tools

Technosynthèse and Anti-Smoke

ISO-L-EGD - JASO FC - API TC

TYPE OF USE

**Specially Formulated for 2 Stroke Engine Garden Tools
Suitable with leaded or unleaded gasoline.**

Motor cultivator, chain saw, lawn mower, ground clearing machine...

GARDEN 2T Hi-Tech exceeds specifications of ISO-L-EGD, JASO FC and API TC standards, and is consequently recommended for engines working under very severe conditions or at high rating.

PERFORMANCE

STANDARDS : ISO-L-EGD , JASO FC , API TC

Contains synthetic products with very high combustion properties to reduce smoke and deposits.

Pre-diluted lubricant which mixes instantaneously with gasoline and remains stable.

Reinforced anti-rust and anti-corrosion properties.

Reduces deposits in exhaust pipes and on pistons.

Prevents spark plug from fouling.

RECOMMENDATIONS

Premix ratio : from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements.

PROPERTIES

Technosynthèse lubricant.

Colour the gasoline in red.

Density at 15°C (59°F)	ASTM D1298	0.867
Viscosity at 40°C (104°F)	ASTM D445	66.5 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	9.9 mm ² /s
Viscosity index	ASTM D2270	130
Flash point	ASTM D92	117°C / 243°F