



SUZUKI MARINE GEAR OIL 90

Lubricant for Outboard Propeller Box

Extreme Pressure

TYPE OF USE

Gear lubricant specially designed for use in SUZUKI outboard propeller box.

PERFORMANCE

STANDARD : **API GL-5**

“Extreme Pressure” lubricant for a better wear protection.

90 grade at hot temperature to guarantee oil film thickness under severe conditions at high load and high temperature. Help to reduce propeller box noise.

High shear resistance to keep lubricant original performances at high temperature.

High lubricating properties for friction reduction.

Anti-corrosion protection.

Anti-foam properties.

RECOMMENDATIONS

Drain interval : according to SUZUKI's recommendations and tune to your own use.

PROPERTIES

Viscosity grade	SAE J300	90
Density at 20°C (68°F)	ASTM D1298	0.898
Viscosity at 40°C (104°F)	ASTM D445	186 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	17 mm ² /s
Viscosity index	ASTM D2270	97
Flash point	ASTM D92	203°C / 397°F
Pour point	ASTM D97	-25°C / -13°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel 33 1 48 11 70 00 - FAX 33 1 48 33 28 79 . Web Site: www.motul.fr

07/09