



# 100 MOTO MIX 2T

**Lubricant for 2 Stroke engines**

**Lubrication by oil injector or premix**

**Mineral**

## TYPE OF USE

Any 2 stroke bike, trails, off road bikes, mopeds... fitted with small displacement 2 stroke engines. Suitable for oil injector systems or premix, leaded or unleaded gasoline

## PERFORMANCE

STANDARDS                      API TC  
    JASO FB level

Lubricant intended to be used with oil injector systems, viscosity as required by bike manufacturers. Minimise deposits on engine internal components and exhaust pipes. Prevents spark plug from fouling.

Instantaneous and stable mixing with gasoline.

## RECOMMENDATIONS

Premix ratio : from 3% to 4% (from 33:1 to 25:1) according to manufacturers' requirements. Adjust according to your own use.

## PROPERTIES

Colour	Visual	Green
Density at 20°C (68°F)	ASTM D1298	0.875
Viscosity at 100°C (212°F)	ASTM D445	9.3 mm <sup>2</sup> /s
Viscosity at 40°C (104°F)	ASTM D445	69.8 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	110
Flash point	ASTM D92	132°C / 297°F
Pour point	ASTM D97	-27°C / -17°F
TBN	ASTM D 2896	1.2 mg KOH/g