



# 7000 4T 10W-40

**Lubricant for 4-Stroke Motorcycle Engine  
Sport & Commuting  
100% Synthetic**

## **TYPE OF USE**

All 4-Stroke Motorbikes.

Road and Off Road Bikes, Trails, 4-Stroke Cross/Enduro Bikes, Quads, Scooters, Mopeds...

## **PERFORMANCES**

|               |                              |
|---------------|------------------------------|
| STANDARDS     | API SP                       |
| SPECIFICATION | JASO MA2 under N° M065MOT224 |

100% Synthetic lubricant for improved oil film resistance at high temperatures and high revolutions. Excellent temperature resistance against oxidation to avoid premature oil thickening. Special additive technology provides good friction properties, deposit and wear protection for increased engine life. Anti-wear technology provides outstanding gearbox durability. High detergent & dispersant properties for a clean and durable engine.

JASO MA2 high friction performance ensures the perfect clutch lock up at start-up, acceleration and full speed.  
Easy gear shifting.

## **RECOMMENDATIONS**

Oil change: follow the manufacturers' recommendations and to be adjusted according to the using condition. Can be mixed with synthetic or mineral lubricants.

## **PROPERTIES**

|                            |            |               |
|----------------------------|------------|---------------|
| Viscosity grade            | SAE J 300  | <b>10W-40</b> |
| Density at 20°C (68°F)     | ASTM D4052 | 0.849         |
| Viscosity at 40°C (104°F)  | ASTM D445  | 98.5 mm²/s    |
| Viscosity at 100°C (212°F) | ASTM D445  | 14.9 mm²/s    |
| Viscosity Index            | ASTM D2270 | 159           |
| Pour point                 | ASTM D97   | -40°C         |
| Flash point                | ASTM D92   | 252°C         |
| TBN                        | ASTM D2896 | 6.5 mg KOH/g  |