300V POWER 5W-30

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: **14/02/2022**
S.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	300V POWER 5W-30

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	4-stroke engine lubricant.

Details of the supplier of the safety data sheet

Registered company name	**Motul Asia Pacific Pte Ltd.**
Address	1A International Business Park, #06-03 Singapore 609933 Singapore
Telephone	+65 6565 8100
Fax	+65 6565 8100
Website	http://www.motul.com/sg/
Email	enquiries@motul.com.sg

Details of the local importer

Registered company name	**High Performance Lubricants Ltd**
Address	120 Captain Springs Rd, Onehunga. Auckland 1061
Telephone	09 571 1366

Emergency telephone number

Association / Organisation	**NCEC**
Emergency telephone numbers	Taiwan: +886 2 8793 3212, Japan: +81 3 4578 9341, South Korea: +82 2 3479 8401, Australia: +61 2 8014 4558, New Zealand: +64 9 929 1483/0800 446 881 (toll free), The rest of AP Countries: +65 3158 1074 (24 hrs)

SECTION 2 Hazards identification

Classification of the substance or mixture

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

Classification	Not Applicable

Label elements

Hazard pictogram(s)	Not Applicable
Signal word	**Not Applicable**

Hazard statement(s)

Not Applicable

Supplementary statement(s)

Not Applicable

Precautionary statement(s) General

Page 1 continued...

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
72623-87-1.	25-55	lubricating oils, petroleum C20-50, hydrotreated neutral
2241366-04-9	25-50	octadecane-hexadecane base oil
72623-86-0.	1-10	lubricating oils, petroleum C15-30 hydrotreated neutral
64742-54-7.	1-10	paraffinic distillate, heavy, hydrotreated (severe)
74869-22-0	1-10	lubricating oil, base oil unspecified
Legend:	*1. Classification by vendor; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available*	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: ▸ Wash out immediately with water. ▸ If irritation continues, seek medical attention. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ▸ Immediately remove all contaminated clothing, including footwear. ▸ Flush skin and hair with running water (and soap if available). ▸ Seek medical attention in event of irritation. For thermal burns: ▸ Decontaminate area around burn. ▸ Consider the use of cold packs and topical antibiotics. For first-degree burns (affecting top layer of skin) ▸ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides. ▸ Use compresses if running water is not available. ▸ Cover with sterile non-adhesive bandage or clean cloth. ▸ Do NOT apply butter or ointments; this may cause infection. ▸ Give over-the counter pain relievers if pain increases or swelling, redness, fever occur. For second-degree burns (affecting top two layers of skin) ▸ Cool the burn by immerse in cold running water for 10-15 minutes. ▸ Use compresses if running water is not available. ▸ Do NOT apply ice as this may lower body temperature and cause further damage. ▸ Do NOT break blisters or apply butter or ointments; this may cause infection. ▸ Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape. To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort): ▸ Lay the person flat. ▸ Elevate feet about 12 inches. ▸ Elevate burn area above heart level, if possible. ▸ Cover the person with coat or blanket. ▸ Seek medical assistance. For third-degree burns Seek immediate medical or emergency assistance. In the mean time: ▸ Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound. ▸ Separate burned toes and fingers with dry, sterile dressings. ▸ Do not soak burn in water or apply ointments or butter; this may cause infection. ▸ To prevent shock see above. ▸ For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway. ▸ Have a person with a facial burn sit up. ▸ Check pulse and breathing to monitor for shock until emergency help arrives.
Inhalation	▸ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▸ Other measures are usually unnecessary.
Ingestion	▸ Immediately give a glass of water. ▸ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Continued...

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

Do not use water jets.

Special hazards arising from the substrate or mixture

Fire Incompatibility	‣ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting	‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ Wear full body protective clothing with breathing apparatus. ‣ Prevent, by any means available, spillage from entering drains or water course. ‣ Use water delivered as a fine spray to control fire and cool adjacent area. ‣ Avoid spraying water onto liquid pools. ‣ **DO NOT** approach containers suspected to be hot. ‣ Cool fire exposed containers with water spray from a protected location. ‣ If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	‣ Combustible. ‣ Slight fire hazard when exposed to heat or flame. ‣ Heating may cause expansion or decomposition leading to violent rupture of containers. ‣ On combustion, may emit toxic fumes of carbon monoxide (CO). ‣ May emit acrid smoke. ‣ Mists containing combustible materials may be explosive. Combustion products include: carbon dioxide (CO_2) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes. **CARE**: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Slippery when spilt. ‣ Remove all ignition sources. ‣ Clean up all spills immediately. ‣ Avoid breathing vapours and contact with skin and eyes. ‣ Control personal contact with the substance, by using protective equipment. ‣ Contain and absorb spill with sand, earth, inert material or vermiculite. ‣ Wipe up. ‣ Place in a suitable, labelled container for waste disposal.
Major Spills	Slippery when spilt. Moderate hazard. ‣ Clear area of personnel and move upwind. ‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ Wear breathing apparatus plus protective gloves. ‣ Prevent, by any means available, spillage from entering drains or water course. ‣ No smoking, naked lights or ignition sources. ‣ Increase ventilation. ‣ Stop leak if safe to do so. ‣ Contain spill with sand, earth or vermiculite. ‣ Collect recoverable product into labelled containers for recycling. ‣ Absorb remaining product with sand, earth or vermiculite. ‣ Collect solid residues and seal in labelled drums for disposal. ‣ Wash area and prevent runoff into drains. ‣ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	‣ **DO NOT** allow clothing wet with material to stay in contact with skin

Continued...

	▸ Electrostatic discharge may be generated during pumping - this may result in fire. ▸ Ensure electrical continuity by bonding and grounding (earthing) all equipment. ▸ Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until fill pipe submerged to twice its diameter, then <= 7 m/sec). ▸ Avoid splash filling. ▸ Do NOT use compressed air for filling discharging or handling operations. ▸ Avoid all personal contact, including inhalation. ▸ Wear protective clothing when risk of exposure occurs. ▸ Use in a well-ventilated area. ▸ Prevent concentration in hollows and sumps. ▸ **DO NOT** enter confined spaces until atmosphere has been checked. ▸ Avoid smoking, naked lights or ignition sources. ▸ Avoid contact with incompatible materials. ▸ When handling, **DO NOT** eat, drink or smoke. ▸ Keep containers securely sealed when not in use. ▸ Avoid physical damage to containers. ▸ Always wash hands with soap and water after handling. ▸ Work clothes should be laundered separately. ▸ Use good occupational work practice. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS. ▸ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
Other information	▸ Store in original containers. ▸ Keep containers securely sealed. ▸ No smoking, naked lights or ignition sources. ▸ Store in a cool, dry, well-ventilated area. ▸ Store away from incompatible materials and foodstuff containers. ▸ Protect containers against physical damage and check regularly for leaks. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	▸ Metal can or drum ▸ Packaging as recommended by manufacturer. ▸ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	· **CARE**: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire. · Oil leaks in a pressurized circuit may result in a fine flammable spray (the lower flammability limit for oil mist is reached for a concentration of about 45 g/m3 · Autoignition temperatures may be significantly lower under particular conditions (slow oxidation on finely divided materials.. ▸ Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	lubricating oils, petroleum C20-50, hydrotreated neutral	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	om-Sampled by a method that does not collect vapour.
New Zealand Workplace Exposure Standards (WES)	lubricating oils, petroleum C15-30 hydrotreated neutral	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	om-Sampled by a method that does not collect vapour.
New Zealand Workplace Exposure Standards (WES)	paraffinic distillate, heavy, hydrotreated (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	om-Sampled by a method that does not collect vapour.

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
lubricating oils, petroleum C20-50, hydrotreated neutral	140 mg/m3	1,500 mg/m3	8,900 mg/m3
lubricating oils, petroleum C15-30 hydrotreated neutral	140 mg/m3	1,500 mg/m3	8,900 mg/m3
paraffinic distillate, heavy, hydrotreated (severe)	140 mg/m3	1,500 mg/m3	8,900 mg/m3

Ingredient	Original IDLH	Revised IDLH
lubricating oils, petroleum C20-50, hydrotreated neutral	2,500 mg/m3	Not Available
octadecane-hexadecane base oil	Not Available	Not Available
lubricating oils, petroleum C15-30 hydrotreated neutral	2,500 mg/m3	Not Available
paraffinic distillate, heavy, hydrotreated (severe)	2,500 mg/m3	Not Available
lubricating oil, base oil unspecified	Not Available	Not Available

Occupational Exposure Banding

Continued...

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
octadecane-hexadecane base oil	E	≤ 0.1 ppm
lubricating oil, base oil unspecified	C	> 1 to ≤ 10 parts per million (ppm)
Notes:	*Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.*	

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
The basic types of engineering controls are:
Process controls which involve changing the way a job activity or process is done to reduce the risk.
Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.
An approved self contained breathing apparatus (SCBA) may be required in some situations.
Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Personal protection



Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Skin protection

See Hand protection below

Hands/feet protection

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:
· frequency and duration of contact,
· chemical resistance of glove material,
· glove thickness and
· dexterity
Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).
· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

Continued...

	· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. · Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Body protection	See Other protection below
Other protection	▸ Overalls. ▸ P.V.C apron. ▸ Barrier cream. ▸ Skin cleansing cream. ▸ Eye wash unit.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.
Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Amber coloured liquid; does not mix with water.

Physical state	Liquid	**Relative density (Water = 1)**	<1
Odour	Not Available	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	Not Applicable	**Decomposition temperature**	Not Available
Melting point / freezing point (°C)	Not Applicable	**Viscosity (cSt)**	64.2 @40C
Initial boiling point and boiling range (°C)	Not Available	**Molecular weight (g/mol)**	Not Applicable
Flash point (°C)	>100	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	Not Applicable	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	Not Available	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	Not Available	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Immiscible	**pH as a solution (Not Available%)**	Not Applicable
Vapour density (Air = 1)	Not Available	**VOC g/L**	Not Available

Continued...

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▸ Unstable in the presence of incompatible materials. ▸ Product is considered stable. ▸ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation hazard is increased at higher temperatures. Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
Ingestion	The material has **NOT** been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Open cuts, abraded or irritated skin should not be exposed to this material The material may accentuate any pre-existing dermatitis condition Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet. Repeated application of mildly hydrotreated oils (principally paraffinic), to mouse skin, induced skin tumours; no tumours were induced with severely hydrotreated oils.

300V POWER 5W-30	**TOXICITY**	**IRRITATION**
	Not Available	Not Available
lubricating oils, petroleum C20-50, hydrotreated neutral	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: >2000 mg/kg[2]	Eye: no adverse effect observed (not irritating)[1]
	Inhalation(Rat) LC50; 2.18 mg/l4h[2]	Skin: no adverse effect observed (not irritating)[1]
	Oral (Rat) LD50; >5000 mg/kg[2]	
octadecane-hexadecane base oil	**TOXICITY**	**IRRITATION**
	dermal (rat) LD50: >2000 mg/kg[2]	Not Available
	Oral (Rat) LD50; >2000 mg/kg[1]	
lubricating oils, petroleum C15-30 hydrotreated neutral	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: >2000 mg/kg[2]	Eye: no adverse effect observed (not irritating)[1]
	Inhalation(Rat) LC50; 2.18 mg/l4h[2]	Skin: adverse effect observed (irritating)[1]
	Oral (Rat) LD50; >5000 mg/kg[2]	Skin: no adverse effect observed (not irritating)[1]
paraffinic distillate, heavy, hydrotreated (severe)	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: >2000 mg/kg[2]	Eye: no adverse effect observed (not irritating)[1]
	Inhalation(Rat) LC50; 2.18 mg/l4h[2]	Skin: no adverse effect observed (not irritating)[1]
	Oral (Rat) LD50; >5000 mg/kg[2]	
lubricating oil, base oil unspecified	**TOXICITY**	**IRRITATION**
	Dermal (rabbit) LD50: >2000 mg/kg[2]	Eye: no adverse effect observed (not irritating)[1]
	Inhalation(Rat) LC50; 2.18 mg/l4h[2]	Skin: no adverse effect observed (not irritating)[1]
	Oral (Rat) LD50; >5000 mg/kg[2]	
Legend:	*1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances*	

Continued...

SECTION 12 Ecological information

Toxicity

300V POWER 5W-30

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

lubricating oils, petroleum C20-50, hydrotreated neutral

Endpoint	Test Duration (hr)	Species	Value	Source
NOEC(ECx)	504h	Crustacea	>1mg/l	1
EC50	48h	Crustacea	>1000mg/l	1

octadecane-hexadecane base oil

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

lubricating oils, petroleum C15-30 hydrotreated neutral

Endpoint	Test Duration (hr)	Species	Value	Source
NOEC(ECx)	504h	Crustacea	>1mg/l	1
EC50	48h	Crustacea	>1000mg/l	1

paraffinic distillate, heavy, hydrotreated (severe)

Endpoint	Test Duration (hr)	Species	Value	Source
NOEC(ECx)	504h	Crustacea	>1mg/l	1
ErC50	72h	Algae or other aquatic plants	>1000mg/l	1

Continued...

	EC50	48h	Crustacea	>1000mg/l	1
	EC50	96h	Algae or other aquatic plants	>1000mg/l	1

lubricating oil, base oil unspecified

Endpoint	Test Duration (hr)	Species	Value	Source
NOEC(ECx)	504h	Crustacea	>1mg/l	1
EC50	48h	Crustacea	>1000mg/l	1
EC50	96h	Algae or other aquatic plants	>1000mg/l	1

Legend: *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data*

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- **DO NOT** allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Not applicable as substance/ material is non hazardous.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
lubricating oils, petroleum C20-50, hydrotreated neutral	Not Available
octadecane-hexadecane base oil	Not Available
lubricating oils, petroleum C15-30 hydrotreated neutral	Not Available
paraffinic distillate, heavy, hydrotreated (severe)	Not Available
lubricating oil, base oil unspecified	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type

Continued...

lubricating oils, petroleum C20-50, hydrotreated neutral	Not Available
octadecane-hexadecane base oil	Not Available
lubricating oils, petroleum C15-30 hydrotreated neutral	Not Available
paraffinic distillate, heavy, hydrotreated (severe)	Not Available
lubricating oil, base oil unspecified	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

HSR Number	Group Standard
Not Applicable	Not Applicable

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.
regulatory lists

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
New Zealand - NZIoC	Listed

Continued...

SECTION 16 Other information

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average PC—
STEL: Permissible Concentration-Short Term Exposure LimitIARC:
International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit。
IDLH: Immediately Dangerous to Life or Health Concentrations
ES: Exposure Standard
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index
AIIC: Australian Inventory of Industrial Chemicals
DSL: Domestic Substances List
NDSL: Non-Domestic Substances List
IECSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory
NZIoC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances
TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas
NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

end of SDS