



710 2T

High-Performance 2-Stroke Engine Lubricant

Premix or injector systems

100% Synthetic – Ester

TYPE OF USE

710 2T is a premium fully synthetic lubricant designed for all high-performance 2-stroke engines, including motorcycles and mopeds, race bikes, trail and off-road bikes, scooters and ATVs operating at high RPMs under severe conditions, whether equipped with an injection system or carburetors.

This oil is suitable for premix or engines fitted with an oil pump and injector and can be used with all types of gasoline fuels – leaded or unleaded, with or without ethanol, and biofuels. It is fully compatible with catalytic converters.

PERFORMANCE

STANDARDS	API TC ISO-L-EGD
SPECIFICATIONS	JASO FD (under N° 033MOT076)

The Japanese JASO M345 standard is based on four engine bench tests designed to evaluate key 2-stroke lubricant properties: lubricity, detergency, smoke reduction, and deposit control. JASO FD represents the highest level within this standard, providing superior engine cleanliness compared to JASO FC.

- 100% synthetic ester-based formula engineered for high-RPM engines, ensuring a durable oil film to protect against wear.
- Reduces internal friction for enhanced power output.
- Formulated for clean combustion to minimize smoke and deposits.
- Mixes instantly and remains stable with gasoline.

RECOMMENDATIONS

Mixing ratio: 2% to 4% (50:1 to 25:1) according to manufacturer specifications.
Adjust the ratio based on your specific use and operating conditions.

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D4052	0.882
Viscosity at 40°C (104°F)	ASTM D445	73.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11.1 mm ² /s
Viscosity Index	ASTM D2270	144
Flash point	ASTM D92	153°C / 307.4°F
Pour point	ASTM D97	-39°C / -38.2°F
TBN	ASTM D2896	2.2 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 – France. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: www.motul.com

02/26