

1500W Series



Model		RNS-1500W
Input	DC Voltage	12V or 24V or 48V or 110V
	Voltage Range	10-15VDC or 21-30VDC or 42-60VDC or 92-132VDC
	No Load Current Draw	<0.5
	Efficiency	> 85%
	DC Connector	Cables With Clips or Car Adaptor
Output	AC Voltage	100/110/120VAC or 220/230/240 VAC
	Continuous Power	1500W
	Surge Power	3000W
	Waveform	Pure Sine Wave
	Frequency	50Hz or 60Hz
	AC Regulation	3%
Protection	Low Voltage Alarm	10DC±0.5V or 20.5DC±1V or 44VDC±1V or 100VDC±1V
	Low Voltage Shut Down	9.5DC±0.5V or 19.5DC±1V or 42VDC±1V or 96VDC±5V
	Over Load	Shut Off Output
	Over Voltage Shut Down	15.5V or 30.5V or 61.2V or 120V
	Over Thermal	Shut Off Output Automatically
	Fuses	Short Circuit
Environment	Working Temperature	Between -10 and +50
	Working Humidity	20% ~ 90%RH non-condensing
	Storage Temperature	Between -30 and +70
Package	Machine Size(mm)	328X165X85
	Packing Size(mm)	366X238X145
	Net Weight(kg)	3.56
	Gross Weight(kg)	4.10
	Packing Mode	Carton
Other	Start	Soft Start
	Cooling Ways	Cooling Fan