

Plug-in bridge - FBS 2-6 - 3030336

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Plug-in bridge, pitch: 6.2 mm, width: 10.7 mm, number of positions: 2, color: red

Your advantages

- ✔ The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step



Key Commercial Data

Packing unit	50 pc
Minimum order quantity	50 pc
GTIN	 4 017918 188818
GTIN	4017918188818
Weight per Piece (excluding packing)	1.874 g
Custom tariff number	85369000
Country of origin	Germany
Sales Key	BE2Z2X

Technical data

Technical data

Color	red
Material	Copper
Number of positions	2
Pitch	6.2 mm
Height	23 mm
Width	10.7 mm
Flammability rating according to UL 94	V0
Maximum load current	32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

Plug-in bridge - FBS 2-6 - 3030336

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values