

Catalogue number: **EUR**□□□-□□ □□□**V**

Eureka Installation Contactor 24 & 240 VAC



Eureka Installation Contactors



- Current Rating: 25A, 40A, 63A
- Coil Voltage: 24VAC, 240VAC
- 1, 2 and 4 Pole
- AC1 and AC3 rated
- Din rail mounted
- Rigid Construction
- Choice of main contact configurations
- Ideal for mounting in Load Centres and Distribution Boards.

| Rated Current | | No. of Contacts | | Coil Voltage | |
|---------------|------|-----------------|----------|--------------|--------|
| 225 | 25 A | 11 | 1N0, 1NC | 24 | 24VAC |
| 425 | 25 A | 02 | 2NO | 240 | 240VAC |
| 440 | 40 A | 13 | 1N0, 3NC | | |
| 463 | 63 A | 31 | 3N0, 1NC | | |
| | | 40 | 4N0 | | |
| | | 04 | 4NC | | |
| | | 22 | 2N0, 2NC | | |

Properties

| Properties | EUR225 | EUR425 | EUR440 | EUR463 |
|---------------------------------|--------------------------------|--------|--------|--------|
| Manufacturer | Eureka | | | |
| Product Range | Eureka Installation Contactors | | | |
| Current Rating | AC1 25 A | 25 A | 40 A | 63 A |
| | AC3 9 A | 9 A | 27 A | 30 A |
| Rated Operational Voltage U_i | 240 / 400 V | | | |
| Rated Insulation Voltage U_e | 500 V | | | |
| Standard Compliances | IEC/EN 61095, IEC/EN 60947-4-1 | | | |

Dimensions of EUR225

