

DA-500RM

6 Zone Remote Microphone

Description:

DA-500RM is a remote paging microphone work with DA-*MT series amplifier, which is of 6 zone paging features, its communication distance up to 300 meters through straight CAT6 cable, each amplifier capacity of connection up to 6 units of remote paging microphone, these microphone are connected hand-by hand. These 6 remote paging microphones could be pre-set different priorities by its dipswitch. The remote paging microphone is direct power supplied by the amplifier.

Features:

- ✓ 6 zone remote microphone for paging system.
- ✓ Economy paging station with 6 zone mixer amplifier.
- ✓ Each amplifier capacity of 6 unit remote microphones.
- ✓ Multiple remote microphones cascaded together for use.
- ✓ With 6 zones and one all zones selection buttons.
- ✓ With 6 zone selection indicators.
- ✓ With power, send and busy indicators.
- ✓ With call button to enable the announcement after zone selection.
- ✓ With chime for reminding before announcement.
- ✓ Remote microphone is directly powered by the amplifier.
- ✓ With two RJ45 ports for amplifier and for next remote microphone.
- ✓ With microphone volume control and aux input.
- ✓ With microphone priority dipswitch to set up master and slave units.
- ✓ Straight CAT6 cable for communication up to 300 meters.



Specification:

Model	DA-500RM
Description	6 Zone Remote Microphone
Power Consumption	3W
Zone Capacity	6 Zones
System Capacity	6 Remote microphones
Aux Inputs	350mV, 10kΩ
Mic Input	5mV, 600Ω
Frequency Response	80Hz~16kHz
THD	<1% at RMS,1KHz
S/N Ratio	>70dB
Operating Temp	-20℃ to +70℃
Power Supply	Direct from the amplifier, DC24V, ±20%
Humidity	<95% no condensation
Dimension	172(W)×150(D)×50(H) mm
Weight	0.9kg

Rear Panel:

