24 Volt motor, Suitable for gates up to 4.5 metres and 450kg

SWING GATE OPENERS















-) Uses Elsema's MC card with Eclipse® operating system
-) Ultra quite operation yet powerful
-) Die-cast Aluminium motor cover for great durability
-) Easily adjustable limit switches
-) Battery backup option (iS400D E7)
-) Waterproof cover design
-) Soft start and soft stop
-) Easy installation



Die-cast aluminum cover. Maximum protection against environment






TECHNICAL DATA

Motor voltage	24 Volts DC	
Max gate weight	450kg	
Max gate length	4.5 metres	
Peak thrust	4500N	
Operation stroke	450mm	
Typical gate opening time	10-15sec	
Duty cycle	20%	
Operating temperature	-20°C~50°C	

Typical installation



- 1 Intelligent control box
- 2 iS400 motor
- 3 PE1500 photo electric beam
- 4 Reflector for PE1500
 - Vehicle detector

Kit contents



Intelligent control box with built-in receiver



iS400D dual swing motors with limit switch




3 x Keyring remotes with frequency hopping



Long range reflector type photo electric beam

Dimensions



Ordering Code

PART NUMBERS	DESCRIPTION
iS400D	Dual swing motor kit
iS400 Single swing motor kit	
E7	*Optional battery backup kit

^{*}Please specify battery backup option when ordering

Optional Accessories



PentaCODE® Keypad

Wireless keypad compatible with Penta series of receivers



GSM Gate Opener

Open your gate with your mobile phone for free!



Locking Actuator

- 12 Volts DC
- 50mm Stroke
-) 20mm Stainless
 - Steel Pin

Backup Batteries



24 Volt, 7Ah rechargeable lead acid battery



Vehicle Detector

- 12, 24 or 240 Volts
- 1 or 2 loops
-) Medium or high sensitivity



Flashing Lights

-) 12 or 24 Volts DC
-) Red, Blue & Amber
- 90 Flashes \ min