

## STOUCH2 / 2S

### Touch Keypad/Reader

- Standalone or 26 Bit Wiegand output
- Up to 2000 users
- Door output
- EM/HID/Mifare compatible
- Stylish metal construction
- Vandal and corrosion resistant
- IP68 weather resistant
- Backlit keys, 12-24V DC



### Specifications

Part Number	STOUCH2 (4x3)	STOUCH2S (6x2 Slimline)
Users	Up to 2000	
Standalone mode	Wiegand input, External card reader can be connected	
26 Bit Wiegand mode	Wiegand output, LED and Buzzer control input	
Supported Card formats	125KHz: EM/HID, 13.56MHz: Mifare/NFC (ISO14443A)	
Max. Card reading distance	125KHz: ≤ 50mm, 13.56MHz: ≤ 20mm	
Card output	26~37 Bit Wiegand	
Keypad output	4 bit, 8 bit, Virtual card number	
Backlight	On / Off / Auto	
Dimensions	145(H) x 83(W) x 26(D)mm	160(H) x 45(W) x 26(D)mm
Weather resistance	Fully potted, IP68 rated	
Material	Zinc Alloy body, Reinforced glass panel	
Operating Temperature	-20~60°C	
Operating Humidity	0~95% (no condensation)	
Input Voltage	12~24V DC	
Idle Current	≤ 50mA	

