

Part No: MC146-W

Description	Stranded 21AWG PACW, 6C, PVC Insulation, PVC Sheath.
Applicable Standards	AS/CA S-008, BS4737-3.30, AS 1049
Suitable Applications	For inter-connecting wiring, suitable for use in Security/Intruded Alarm system; Use in low voltage/low current applications such as intercommunication.
	Not suitable for mains connection.

Security Cable


Cable Construction Drawing



Picture is for illustration only.
For actual jacket colours, please refer to Packing Table.



Cable Construction Relative Parts



Cable Description

Conductor	No. of Strands	Strand Size	Material
	14	0.2mm	PACW
Insulation	Cores:	6	
	Material:	V-75 PVC	
	Colour:	White, Blue, Red, Black, Yellow, Green	
	Nominal Diameter:	1.5 mm	
	Nominal Thickness:	0.4 mm	

With Garland, you are always well connected.



garland

Sheath	Material:	4V-75 PVC
	Colour:	Refer to Packing Table
	Nominal Diameter:	6.1 mm
	Nominal Thickness:	0.6 mm

Electrical Properties

Voltage Rating	ELV
----------------	-----

Mechanical Properties

Operating Temperature Range	-15 to 75°C
Max. Recommended Pulling Tension	160N
Min. Bend Radius (install)	60 mm
Approximate Mass	5.5 kg/100m

SKU	Jacket Colour	Length (Metres)	Carton/Box Size (cm)	Reels/Carton	Boxes x Reels per Pallet
MC146WH100W	White	100	46 x 24 x 15.5	4	24 x 4
MC146WH250BW	White	250	36 x 36 x 21	-	36
MC146BK250BW	Black	250	36 x 36 x 21	-	36

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

With Garland, you are always well connected.

Sales Enquiries **1800 66 99 99**
www.garlandcables.com.au

MC146-W-150311.docx

made by



madison