



B6K2 -EHPLUS

Keypad & Reader

Two output combination unit


- Standalone, Up to 20,000 users
- Wiegand input and output
- 2x relay outputs
- Stylish metal construction
- Vandal and corrosion resistant
- IP68 weather resistant
- Backlit keys
- 10~28V AC/DC



Compatible with
HID format prox
cards & fobs

Keypad & Reader

Two output combination unit



Specifications

Two relay Operation

- Suitable for two doors, or one door with door bell
- Relay of both zones can be programmed for 3 modes:
Card, PIN, Card + PIN

Multi Modes

- Read both EM & HID 125KHz card
- Toggle Mode, Pulse Mode

Wiegand Input & Output

- 26-37 Bit Wiegand input & output

Up to 20,000 Users

- Up to 20,000 user cards and PIN codes
- Up to 21 manager cards can be set

Other Specs

- 4~8 digits variable PIN length
- Adjustable door output time, alarm time, door open time
- Adjustable Site Code, backlight, LED and buzzer
- Card block enrollment
- IP68 Weather Resistant
- Strong zinc alloy electroplated anti-vandal case
- 10~28V AC/DC
- 35mA @ 12V DC (standby) | 100mA @ 12V DC (operating)
- Product dimension: 128 (H) mm x 82 (W) mm x 28 (D) mm

