

**DS-PDMC-EG2-WB-BLK**  
**Magnetic Contact**



- Slim design for an unobtrusive (unnoticeable) installation
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission

## ▪ Specification

Model		DS-PDMC-EG2-WB-BLK
<b>Detection Performance</b>	Detection Method	Opening Contact
	Detection Gap	43mm Max
<b>Feature</b>	Digital Processing	Support
	Tamper Protection	Front,Rear
	Environment Temperature Indicator	Support
	Signal Strength Indicator	Support
<b>Interface</b>	Alarm Input	Normally Closed,Normally Open,Impulse Count
	Power Switch	Power Up Enrolling
	LED Indicator	Blue (Alarm)
<b>Transmission</b>	Transmission Technology	Tri-X Wireless
	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	433MHz
	Transmission Security	Support
	Transmission Range(Free Space)	1.2Km
	Frequency Hopping	Support
	Enrolling Method	Power up,Remote ID,QR Code
<b>Electrical Characteristics</b>	Standard Battery Life	Up to 5 years (standby time)
	Power Supply	Battery Powered
	Battery Type	CR123A x 1
	Typical Voltage	3V
<b>General</b>	Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%

	Dimension(W xHxD)	24mm × 104mm × 24.4mm 13mm × 34.4mm × 11.4mm
	Weight	59g
	Application Scenario	Indoor

▪ **Available Model**

DS-PDMC-EG2-WB(B)

DS-PDMC-EG2-WB(B)/BLACK

▪ **Accessory**

▪ **Optional**

DS-PDB-MC-Brown (B) Magnetic Contact Brown Housing	DS-PDB-MC-Adapter Magnetic Contact Adapter	DS-PDP-IN-CR123A Indoor Detector Battery	DS-PWA96-Kit-WB/ 12V AX PRO Kit (433MHz)	DS-PDB-MC-Brown Magnetic Contact Brown Housing
				

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

