xtendr

XTR-C5USBPR02-SX

HDMI Extender with USB KVM

Extends 50m over single Cat5e/Cat6 cable

Features:

HDMI extender with USB KVM

HDMI video resolution up to 1080p
@ 60Hz, 1.65Gbps bandwidth

- Transmission range up to 50m
- 4x USB2.0 pass through
- HCDCP 1.4 compliant
- Supports Dual POC
- 12V DC power supply



Specifications:

Operating Temperature Range	-10 to +45°C(14 to +113°F)
Storage Temperature Range	-15 to +70°C(5 to +158°F)
Operating Humidity Range	5 to 90%RH (No Condensation)
Support Video Format	DTV/HDTV: 480P/576P/720P/1080P
	VESA:640x480, 800x600, 1024x768, 1280x1024,
	1680x1050, 1280x720, 1360x768
Connector on Transmitter	1x HDMI Input, 1x USB B Type
	1xRJ45 Output
Connector on Receiver	1xRJ45 Input
	1x HDMI Output, 4x USB A Type
Transmission Distance	100m (Max) over single Cat5e/6 /24AWG/Solid under Non-USB Mode
	50m(Max) over Single Cat5e/6 /24AWG/Solid under USB Mode
USB Transmit speed	480M bit/s (Max)
Power consumption	4.8W(Max)
Dimension (L×W×H)	L147.5xW73.6xH22mm
Net Weight	Transmitter:257.5g; Receiver:257.5g