



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE AFC22603

2. DESCRIPTION 2 Core Parallel Webbed (Figure 8) 23/.32 (1.84mmsq) P.A.C.W,
V90 PVC insulated. L.D.P.E insulated.
Extra low voltage automotive cable, Not for mains outlet connection.

3. CONSTRUCTION

3.1 CONDUCTOR: 23 strands of 0.32 mm Plain Annealed Copper to
AS1125 drawn from Class 102 copper to AS1574.

Max. DC Resistance at 20C : 10.1 ohms/km

3.2 INSULATION: Coloured V90 PVC to AS3808.
Parallel Webbed (Figure 8) construction.

Nominal Diameter: 3.1 x 6.7mm

Nominal Wall Thickness: 0.6mm