

DS-2TR03-50UM/W Thermal Scope



















Hikvision DS-2TR03-50UM/W Thermal Scope has 384×288 thermal detector and 1024×768 OLED monitor, which provides clear image under harsh environment conditions like darkness, fog, smoke, dust, rain, snow, wood, camouflage, etc. The shutterless technology avoids the risk of target losing and self-exposure which was caused by shutter. These all make great efforts to better observe target situation and fight against crimes.

Key Features

- 384*288 thermal resolution, high sensitivity detector, NETD < 40mk (@25°C,F#=1.0)
- Adopt shutterless technology
- Leading image processing technology: Adaptive AGC, DDE, 3D DNR
- 1024*768 resolution 0.39-inch OLED display
- Support distance measurement, GPS and WIFI hotspot function
- Support video recording and snapshot, build in Micro SD memory module (Max 16GB)
- Support digital zoom and crosshair function, palettes of color adjustable
- Over 8 hours battery operating time





Specification

	Model	DS-2TR03-50UM/W		
Parameter		Thermal Scope		
	Image Sensor	Uncooled Focal Plane Arrays		
	Max. Resolution	384*288, 17um		
	Response Waveband	8~14um		
Thermal	NETD	< 40mk(@25 °C, F#=1.0)		
Module	Lens (focal length)	50mm (support manual focus)		
	IFOV	0.34mrad		
	Field of View	7.4°×5.6°		
	F Number	F1.0		
Image	Monitor	0.39-inch, OLED, 1024 ×768		
	Palettes	Black hot, white hot, red hot		
Display	Ocular Exit Pupil Distance	30 mm		
	Digital Zoom	2X, 4X		
	Crosshair	Support		
	WIFI	Support		
	Distance Measurement	Support		
	GPS	Support		
System	Video Recording	Support		
	Picture Snapshot	Support		
	Contrast Adjustment	Support		
	Brightness Adjustment	Support		
	Uniformity Correction	Support shutterless technology		
	Storage	Built-in Micro SD memory module (Max 16GB)		
	Battery	Two 18650 batteries, require 5h to be full charged		
	Power Consumption	≤2.1W		
Power	Battery Operating Time	≥8h		
Supply	Anti-reverse battery connection	Support		
	Overvoltage Protection	Support		
	Battery Capacity Display	Support		
General	Mounting	Picatinny rail system		
	Port	USB, analog video output		
	Working Temperature	-30°C ~55°C (-22°F ~ 131°F)		
	Protection Level	IP67		
	Shock Absorption Design	Support		
	Prevent Ocular Light Leak	Support		
	Vibration & Shock	MIL-STD-810F		
	Electrostatic Protection	15KV		
	Dimension (L x W x H)	244mm x 65mm x 95mm (9.61" x 2.56" x 3.74")		
	Weight	< 0.8kg		



Wide Range Coverage for Different Specifications

Note: The table below is only for reference, the performance varies from model to model, and the specific data is based on 17 µm pixel space-between.

Detection	Detection	Recognition	Recognition	Identification	Identification	
Range	Range	Range	Range	Range	Range	
(Vehicles:	(Humans:	(Vehicles:	(Humans:	(Vehicles:	(Humans:	
1.4×4.0m)	1.8×0.5m)	1.4×4.0m)	1.8×0.5m)	1.4×4.0m)	1.8×0.5m)	
4510m	1471m	1127m	368m	564m	184m	

Order Models

DS-2TR03-50UM/W

Distributed by			
			_



Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T+90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T+7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com


Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com


Hikvision Colombia sales.colombia@hikvision.com



Dimensions







Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400

T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233

salesau@hikvision.com Hikvision India

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com

Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com

Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com

Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T+7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com