

DS-PD2-P18CE PIR Detector

DS-PD2-P18CE has a long narrow coverage pattern that makes it ideal for protecting shop fronts and large windows. With Bluewave technology, auto sensitivity and digital temperature compensation the DS-PD2-P18CE will keep you protected, automatically adjusting the detector to match the environmental conditions such as infra-red noise, light and temperature.



AVAILABLE MODEL

DS-PD2-P18CE

MAIN FEATURES

- 18m digital curtain detection coverage
- Dual element pyro-electric sensor
- Selectable EOL (End Of Line) resistors
- Blue wave technology
- Auto sensitivity feature
- Digital temperature compensation
- Tamper-proof of front shell

PIR Detector www.hikvision.com

SPECIFICATION

PIR Detector	
Detection Range	18m or 30m long range, coverage angle: 20°
Detection Speed	0.3m/s ~ 3.0m/s
Detection zones	46 curtain coverage or 24 long range
Power Supply	9-16V DC 13.8V DC typical
Operation Temperature	-30℃ ~+70℃
Dimension(L*W*H)	117mm*69mm*50mm
Weight	125g (without bracket)
Installation Environment	Indoor
Optimum coverage height	Max 4m (curtain coverage) or 1.8M ~ 2.4m (long range coverage)

^{*}Including 1 x Ceiling mounting bracket, 1 x Wall mounting bracket