

# Hikvision L Series Micro SD (TF) Card for Surveillance

## Introduction

Hikvision L Series Micro SD (TF) Card for Surveillance is specially designed for video surveillance recording with a Class 10 read-write speed. It adopts TLC NAND with high compatibility and low price, widely applicable to low video recording intensity scenes with lite storage, standby storage, etc. or scenes with simple operating environment.



## Available Models

DS-UTF16GI-L1  
DS-UTF32GI-L1  
DS-UTF64GI-L1  
DS-UTF128GI-L1

## Main Features

### ● High cost performance

Lower price when compared to the card with the same TLC NAND, fully satisfying requirement for lite storage, which is the storage used for low intensity video recording and simple scenes;

### ● High compatibility

Better compatibility with more products. It can be optimized according to Hikvision storage system. Better effect when used with Hikvision cameras;

### ● Ultrastrong adaptability

Waterproof, shock proof, X-ray proof, and temperature proof to perform normally in various harsh environments.

## Specifications

| Capacity                 | 16 GB<br>(microSD<br>HC)   | 32 GB<br>(microSD<br>HC) | 64 GB<br>(microSD<br>XC) | 128 GB<br>(microSD<br>XC) |
|--------------------------|--|--------------------------|--------------------------|---------------------------|
| Performance/<br>Speed    | Class 10; 25MB/s read and 20MB/s write   |                          |                          |                           |
| Card<br>Dimensions       | 14.99 mm × 10.92 mm × 1.02 mm<br>(0.59" × 0.43" × 0.04")                               |                          |                          |                           |
| Operating<br>temperature | -0°C to 70°C   |                          |                          |                           |
| Storage<br>temperature   | -25°C to 85°C  |                          |                          |                           |
| Compatibility            | Compatible with microSDHC, microSDXC, microSDHC UHS-I and microSDXC UHS-I host devices |                          |                          |                           |
| Warranty                 | 2-year limited warranty  |                          |                          |                           |