

IXG-DM7-HIDA

IP Video Entrance Station

The IXG-DM7-HIDA is an IP video entrance station for the IX|IXG Series multi-tenant system. It is equipped with a 7" LCD directory screen that can be used to call a tenant or enter an access code.

Up to 9,999 names/numbers can be stored in the station. A motion sensor will activate the screen when the visitor approaches. Once a call is placed, the visitor will be displayed on the tenant station or app using the 720p HD camera.

The station is equipped with an HID® card reader for card access. It supports Prox or iCLASS® 26 bit cards. Up to 10 entrance stations can be assigned per unit and multiple units can be supported by one system.



- 7" touchscreen
- PoE compliant
- On-board recording with microSD™ card
- Simple user interface
- Hands-free communication
- 720p HD camera
- Up to 9,999 names/numbers can be stored
- Programmable contact inputs and outputs
- T-coil hearing aid compatibility
- Motion sensor to activate LCD
- Built-in HID® reader for card access, supports 26-bit Wiegand formats only
- Stainless steel panel
- Rugged IP65 and IK08 ratings

Power Source	PoE (IEEE 802.3af Class 0)	Material	Stainless steel
Power Draw	4.2W standby, 12.7W max	Door Release	Two programmable Form C dry contacts, 24V AC/DC
Video Display	7" TFT LCD touchscreen (800x400 resolution)		Relay 1: 3A
Communication	Hands-free (full-duplex)		Relay 2: 500mA
Camera	720p HD	Mounting	Flush mount with IXG-DM7-BOX or surface mount with SBX-IXGDM7
Audio Codec	G.711 (μ-law, A-law)	Wire Type	Cat-5e or Cat-6
Video Codec	H.264	Distance	Entrance Station, Tenant Station, or Guard Station to Network Drop: 330'
Protocols	IPv4/v6, TCP, UDP, SIP, HTTP, HTTPS, RTSP, RTP/RTCP, IGMP, MLD, SMTP, SFTP, DHCP, NTP, DNS, TLS	Protection	IP65, IK08
Operating Temp	-22°~140°F (-30°~60°C)	Dimensions	13-11/16" H 7-3/16" W
HID® Reader	High Frequency (13.56MHz): iCLASS, SEOS, iCLASS SR, iCLASS SE, MIFARE Classic, MIFARE DES Fire EV1 Low Frequency (125kHz): HID® Proximity		